

SML-LX1206GC-TR

SML-LX1206GC-TR Information

Man Cate	nufacturer egory cription	SML-LX1206GC-TR Lumex Opto/Components Inc. Optoelectronics LED Indication - Discrete LED GREEN CLEAR 1206 SMD 1206 (3216 Metric) For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SML-LX1206GC-TR Specifications

Manufacturer Lumex Opto/Components Inc. Manufacturer Optoelectronics LED Indication - Discrete Package 1206 (3216 Metric) Series - Color Green Color Colorless Lens Color Colorless Lens Style/Size Rectangle with Flat Top, 2.00mm x 1.50mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Mounting Type Surface Mount Wavelength - Dominant - Features - Package / Case 206 (3216 Metric) Surface Mount - Mavelength - Dominant - Features - Package / Case 206 (3216 Metric) Supplier Device Package 1206 (3216 Metric) Supplier Device Package 1206 (3216 Metric) Size / Dimension 3.20mm L x 1.60mm W		
Optoelectronics LED Indication - Discrete Package 1206 (3216 Metric) Series - Color Green Configuration - Lens Color Colorless Lens Style/Size Rectangle with Flat Top, 2.00mm x 1.50mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Wavelength - Dominant - Wavelength - Peak 565mm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 1206 (3216 Metric) Supplier Device Package 1206 (3216 Metric) Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.10mm	Manufacturer Part Number	SML-LX1206GC-TR
LED Indication - DiscretePackage1206 (3216 Metric)Series-ColorGreenConfiguration-Lens ColorColorlessLens TansparencyClearMillicandela Rating10mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.50mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Manufacturer	Lumex Opto/Components Inc.
Package1206 (3216 Metric)Series-ColorGreenConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating10mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.50mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAWouting Type60°Mounting Type565nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.00mm	Category	Optoelectronics
Series-ColorGreenConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating10mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.50mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAWoutning TypeSurface MountWavelength - Poak565mmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm		LED Indication - Discrete
ColorGreenConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating10mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.50mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant-Verkage / Case555nmPackage / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.10mm	Package	1206 (3216 Metric)
Configuration-Lens ColorColorlessLens TransparencyClearMillicandela Rating10mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.50mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating10mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.50mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant-Verkenger Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Color	Green
Lens TransparencyClearMillicandela Rating10mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.50mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mACurrent - Test00mAWouting Type60°Mounting TypeSurface MountWavelength - Dominant-Features-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.10mm	Configuration	-
Millicandela Rating10mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.50mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak565nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.10mm	Lens Color	Colorless
Lens Style/SizeRectangle with Flat Top, 2.00mm x 1.50mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak565nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak565nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Millicandela Rating	10mcd
Current - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak565nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Lens Style/Size	Rectangle with Flat Top, 2.00mm x 1.50mm
Viewing Angle160°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak565nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Voltage - Forward (Vf) (Typ)	2.2V
Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak565nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Current - Test	20mA
Wavelength - Dominant-Wavelength - Peak565nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Viewing Angle	160°
Wavelength - Peak565nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Mounting Type	Surface Mount
Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Wavelength - Dominant	-
Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Wavelength - Peak	565nm
Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Features	-
Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Package / Case	1206 (3216 Metric)
Height (Max) 1.10mm	Supplier Device Package	1206
	Size / Dimension	3.20mm L x 1.60mm W
Report errors?	Height (Max)	1.10mm
		Report errors?

SML-LX1206GC-TR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SML-LX1206GC-TR Payment Methods



SML-LX1206GC-TR Shipping Methods



If you have any question about SML-LX1206GC-TR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com