

Heisener.com

# SML-LXL505SOC-TR

### **SML-LXL505SOC-TR Information**

Part Number SML-LXL505SOC-TR

Manufacturer Lumex Opto/Components Inc.

Category Optoelectronics

LED Indication - Discrete

**Description** LED ORANGE CLEAR 4SMD

4-SMD, Flat Leads **Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **SML-LXL505SOC-TR Specifications**

Manufacturer Part Number  Manufacturer  Lumex Opto/Components Inc.  Optoelectronics  LED Indication - Discrete  Package  4-SMD, Flat Leads  Series  - Color  Orange  Configuration  - Lens Color  Colorless  Lens Transparency  Millicandela Rating  Lens Style/Size  Round with Domed Top, 5mm (T-1 3/4), 5.00mm  Voltage - Forward (Vf) (Typ)  2V  Current - Test  20mA  Viewing Angle  Mounting Type  Surface Mount  Wavelength - Dominant  Wavelength - Peak  Features  Package / Case  4-SMD, Flat Leads		
Category Optoelectronics  LED Indication - Discrete  Package 4-SMD, Flat Leads  Series - Color Orange  Configuration - Lens Color Colorless  Lens Transparency Clear Millicandela Rating 1500mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm  Voltage - Forward (Vf) (Typ) 2V  Current - Test 20mA  Viewing Angle 30°  Mounting Type Surface Mount  Wavelength - Dominant - Wavelength - Peak 610nm  Features - Package / Case 4-SMD, Flat Leads	Manufacturer Part Number	SML-LXL505SOC-TR
LED Indication - Discrete  Package 4-SMD, Flat Leads  Series - Color Orange  Configuration - Lens Color Colorless  Lens Transparency Clear  Millicandela Rating 1500mcd  Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm  Voltage - Forward (Vf) (Typ) 2V  Current - Test 20mA  Viewing Angle 30°  Mounting Type Surface Mount  Wavelength - Dominant - Wavelength - Peak 610nm  Features - Package / Case 4-SMD, Flat Leads	Manufacturer	Lumex Opto/Components Inc.
Package 4-SMD, Flat Leads  Series - Color Orange Configuration - Lens Color Colorless  Lens Transparency Clear Millicandela Rating 1500mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm  Voltage - Forward (Vf) (Typ) 2V  Current - Test 20mA  Viewing Angle 30°  Mounting Type Surface Mount  Wavelength - Dominant - Wavelength - Peak 610nm  Features - Package / Case 4-SMD, Flat Leads	Category	Optoelectronics
Series - Color Orange Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 1500mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 30° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case 4-SMD, Flat Leads		LED Indication - Discrete
Color Configuration - Lens Color Colorless Lens Transparency Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle Mounting Type Surface Mount Wavelength - Dominant Wavelength - Peak Features Package / Case  Orange Corrage Colorless Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm V-1 3/4), 5.00mm  Surface Mount Tople Surface Mount - Valvelength - Dominant - Valvelength - Peak - Package / Case 4-SMD, Flat Leads	Package	4-SMD, Flat Leads
Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 1500mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 30° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 610nm Features Package / Case 4-SMD, Flat Leads	Series	-
Lens Color  Lens Transparency Clear  Millicandela Rating 1500mcd  Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm  Voltage - Forward (Vf) (Typ) 2V  Current - Test 20mA  Viewing Angle 30°  Mounting Type Surface Mount  Wavelength - Dominant - Wavelength - Peak 610nm  Features Package / Case 4-SMD, Flat Leads	Color	Orange
Lens TransparencyClearMillicandela Rating1500mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle30°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak610nmFeatures-Package / Case4-SMD, Flat Leads	Configuration	-
Millicandela Rating  Lens Style/Size  Round with Domed Top, 5mm (T-1 3/4), 5.00mm  Voltage - Forward (Vf) (Typ)  2V  Current - Test  20mA  Viewing Angle  30°  Mounting Type  Surface Mount  Wavelength - Dominant  -  Wavelength - Peak  610nm  Features  -  Package / Case  4-SMD, Flat Leads	Lens Color	Colorless
Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm  Voltage - Forward (Vf) (Typ) 2V  Current - Test 20mA  Viewing Angle 30°  Mounting Type Surface Mount  Wavelength - Dominant -  Wavelength - Peak 610nm  Features -  Package / Case 4-SMD, Flat Leads	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) 2V  Current - Test 20mA  Viewing Angle 30°  Mounting Type Surface Mount  Wavelength - Dominant -  Wavelength - Peak 610nm  Features -  Package / Case 4-SMD, Flat Leads	Millicandela Rating	1500mcd
Current - Test 20mA  Viewing Angle 30°  Mounting Type Surface Mount  Wavelength - Dominant -  Wavelength - Peak 610nm  Features -  Package / Case 4-SMD, Flat Leads	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4), 5.00mm
Viewing Angle30°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak610nmFeatures-Package / Case4-SMD, Flat Leads	Voltage - Forward (Vf) (Typ)	2V
Mounting Type Surface Mount  Wavelength - Dominant - Wavelength - Peak 610nm  Features - Package / Case 4-SMD, Flat Leads	Current - Test	20mA
Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case 4-SMD, Flat Leads	Viewing Angle	30°
Wavelength - Peak 610nm  Features - Package / Case 4-SMD, Flat Leads	Mounting Type	Surface Mount
Features - Package / Case 4-SMD, Flat Leads	Wavelength - Dominant	-
Package / Case 4-SMD, Flat Leads	Wavelength - Peak	610nm
-	Features	-
	Package / Case	4-SMD, Flat Leads
Supplier Device Package Surface Mounted Dome LED	Supplier Device Package	Surface Mounted Dome LED
Size / Dimension 6.60mm L x 6.60mm W	Size / Dimension	6.60mm L x 6.60mm W
Height (Max) 5.40mm	Height (Max)	5.40mm
Report errors		Report errors?

## **SML-LXL505SOC-TR Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **SML-LXL505SOC-TR Payment Methods**

































If you have any question about SML-LXL505SOC-TR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com