

Heisener.com

SML-LXL505UPGC-TR

SML-LXL505UPGC-TR Information

Part Number SML-LXL505UPGC-TR Manufacturer Lumex Opto/Components Inc.

Category Optoelectronics

LED Indication - Discrete

Description LED GREEN CLEAR 4SMD

4-SMD, Flat Leads **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SML-LXL505UPGC-TR Specifications

Manufacturer Part Number Manufacturer Lumex Opto/Components Inc. Optoelectronics LED Indication - Discrete Package 4-SMD, Flat Leads Series Color Green Configuration Lens Color Lens Transparency Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 3.5V Current - Test 20mA Viewing Angle Mounting Type Wavelength - Dominant Wavelength - Peak Features Package / Case Optoelectronics Lemex Opto/Components Inc. Optoelectronics Lemex Opto/Components Inc. Colorloss LED Indication - Discrete 4-SMD, Flat Leads		
Category Optoelectronics LED Indication - Discrete 4-SMD, Flat Leads Series - Color Green Configuration - Lens Color Constrainsparency Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 3.5V Current - Test Viewing Angle Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak Features - Ogreen Colorless Colorless Round With Domed Top, 5mm (T-1 3/4), 5.00mm 3.5V Current - Test 20mA Surface Mount - Wavelength - Peak 525nm Features	Manufacturer Part Number	SML-LXL505UPGC-TR
LED Indication - Discrete Package 4-SMD, Flat Leads Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 2200mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 3.5V Current - Test 20mA Viewing Angle 30° Mounting Type Surface Mount Wavelength - Dominant Wavelength - Peak 525nm Features -	Manufacturer	Lumex Opto/Components Inc.
Package 4-SMD, Flat Leads Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 2200mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 3.5V Current - Test 20mA Viewing Angle 30° Mounting Type Surface Mount Wavelength - Dominant Wavelength - Peak 525nm Features -	Category	Optoelectronics
Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 2200mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 3.5V Current - Test 20mA Viewing Angle 30° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 525nm Features -		LED Indication - Discrete
Color Configuration - Lens Color Colorless Lens Transparency Millicandela Rating 2200mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 3.5V Current - Test 20mA Viewing Angle Wounting Type Surface Mount Wavelength - Dominant Wavelength - Peak Features -	Package	4-SMD, Flat Leads
Configuration Lens Color Colorless Lens Transparency Clear Millicandela Rating 2200mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 3.5V Current - Test 20mA Viewing Angle Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 525nm Features -	Series	-
Lens Color Lens Transparency Clear Millicandela Rating 2200mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 3.5V Current - Test 20mA Viewing Angle Mounting Type Surface Mount Wavelength - Dominant Wavelength - Peak Features -	Color	Green
Lens TransparencyClearMillicandela Rating2200mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)3.5VCurrent - Test20mAViewing Angle30°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak525nmFeatures-	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 3.5V Current - Test 20mA Viewing Angle Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 525nm Features -	Lens Color	Colorless
Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 3.5V Current - Test 20mA Viewing Angle 30° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 525nm Features -	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) Current - Test 20mA Viewing Angle Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 525nm Features -	Millicandela Rating	2200mcd
Current - Test 20mA Viewing Angle 30° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 525nm Features -	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4), 5.00mm
Viewing Angle30°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak525nmFeatures-	Voltage - Forward (Vf) (Typ)	3.5V
Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 525nm Features -	Current - Test	20mA
Wavelength - Dominant - Wavelength - Peak 525nm Features -	Viewing Angle	30°
Wavelength - Peak 525nm Features -	Mounting Type	Surface Mount
Features -	Wavelength - Dominant	-
	Wavelength - Peak	525nm
Package / Case 4-SMD, Flat Leads	Features	-
,	Package / Case	4-SMD, Flat Leads
Supplier Device Package Surface Mounted Dome LED	Supplier Device Package	Surface Mounted Dome LED
Size / Dimension 6.60mm L x 6.60mm W	Size / Dimension	6.60mm L x 6.60mm W
Height (Max) 5.40mm	Height (Max)	5.40mm
Report error		Report errors?

SML-LXL505UPGC-TR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SML-LXL505UPGC-TR Payment Methods





















SML-LXL505UPGC-TR Shipping Methods













If you have any question about SML-LXL505UPGC-TR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com