

SML-LXR85SYC-TR

SML-LXR85SYC-TR Information



For Reference Only

Part Number SML-LXR85SYC-TR

Manufacturer Lumex Opto/Components Inc.

Category Optoelectronics

LED Indication - Discrete

Description LED YELLOW CLEAR 2SMD R/A

Package 2-SMD, 0805

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SML-LXR85SYC-TR Specifications

Manufacturer Category Optoelectronics LED Indication - Discrete Package 2-SMD, 0805 Series - Color Yellow Configuration - Lens Color Color Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Rectangle with Domed Top, 2.00mm x 1.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test Viewing Angle Mounting Type Surface Mount, Right Angle Wavelength - Peak 590nm		
Category Optoelectronics LED Indication - Discrete Package 2-SMD, 0805 Series - Color Yellow Configuration - Lens Color Color Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Rectangle with Domed Top, 2.00mm x 1.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Wavelength - Peak 590nm	Manufacturer Part Number	SML-LXR85SYC-TR
LED Indication - Discrete Package 2-SMD, 0805 Series - Color Yellow Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Rectangle with Domed Top, 2.00mm x 1.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 160° Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Wavelength - Peak 590nm	Manufacturer	Lumex Opto/Components Inc.
Package 2-SMD, 0805 Series - Color Yellow Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Rectangle with Domed Top, 2.00mm x 1.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 160° Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Wavelength - Peak 590nm	Category	Optoelectronics
Series - Color Yellow Configuration - Colorless Lens Color Clear Millicandela Rating 50mcd Lens Style/Size Rectangle with Domed Top, 2.00mm x 1.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 160° Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Sunday Sund		LED Indication - Discrete
Color Configuration	Package	2-SMD, 0805
Configuration - Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Rectangle with Domed Top, 2.00mm x 1.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 160° Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Wavelength - Peak 590nm	Series	-
Lens Color Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Rectangle with Domed Top, 2.00mm x 1.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Wavelength - Peak 590nm	Color	Yellow
Lens Transparency Millicandela Rating 50mcd Lens Style/Size Rectangle with Domed Top, 2.00mm x 1.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 160° Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Wavelength - Peak 590nm	Configuration	-
Millicandela Rating 50mcd Lens Style/Size Rectangle with Domed Top, 2.00mm x 1.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 160° Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Wavelength - Peak 590nm	Lens Color	Colorless
Lens Style/Size Rectangle with Domed Top, 2.00mm x 1.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 160° Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Wavelength - Peak 590nm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) Current - Test 20mA Viewing Angle Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Wavelength - Peak 590nm	Millicandela Rating	50mcd
Current - Test 20mA Viewing Angle 160° Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Wavelength - Peak 590nm	Lens Style/Size	Rectangle with Domed Top, 2.00mm x 1.00mm
Viewing Angle160°Mounting TypeSurface Mount, Right AngleWavelength - Dominant-Wavelength - Peak590nm	Voltage - Forward (Vf) (Typ)	2V
Mounting Type Surface Mount, Right Angle Wavelength - Dominant - Wavelength - Peak 590nm	Current - Test	20mA
Wavelength - Dominant - Wavelength - Peak 590nm	Viewing Angle	160°
Wavelength - Peak 590nm	Mounting Type	Surface Mount, Right Angle
	Wavelength - Dominant	-
Features -	Wavelength - Peak	590nm
	Features	-
Package / Case 2-SMD, 0805	Package / Case	2-SMD, 0805
Supplier Device Package -	Supplier Device Package	-
Size / Dimension 3.20mm L x 1.60mm W	Size / Dimension	3.20mm L x 1.60mm W
Height (Max) 1.00mm	Height (Max)	1.00mm
Report errors?		Report errors?

SML-LXR85SYC-TR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SML-LXR85SYC-TR Payment Methods



















SML-LXR85SYC-TR Shipping Methods













If you have any question about SML-LXR85SYC-TR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com