



SMP4-BC-RY Information



For Reference Only

Part Number SMP4-BC-RY **Manufacturer** Bivar Inc.

Category Optoelectronics

LED Indication - Discrete

Description LED RED/YLW CLEAR 4PLCC SMD

Package 4-PLCC

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SMP4-BC-RY Specifications

Manufacturer Part Number SMP4-BC-RY Manufacturer Bivar Inc. Category Optoelectronics LED Indication - Discrete Package 4-PLCC Series - Color Red, Yellow Configuration Independent Lens Color Colorless Lens Transparency Clear Millicandela Rating 36mcd Red, 16mcd Yellow Lens Style/Size Round with Flat Top, 2.40mm Voltage - Forward (Vf) (Typ) 1.85V Red, 1.9V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 640mm Red, 585nm Yellow Wavelength - Peak - Features 4-PLCC Supplier Device Package 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	*	
Category Optoelectronics Package 4-PLCC Series - Color Red, Yellow Configuration Independent Lens Color Colorless Lens Transparency Clear Millicandela Rating 36mcd Red, 16mcd Yellow Lens Style/Size Round with Flat Top, 2.40mm Voltage - Forward (Vf) (Typ) 1.85V Red, 1.9V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 640nm Red, 585nm Yellow Wavelength - Peak - Features - Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Manufacturer Part Number	SMP4-BC-RY
Package 4-PLCC Series - Color Red, Yellow Configuration Independent Lens Color Colorless Lens Transparency Clear Millicandela Rating 36mcd Red, 16mcd Yellow Lens Style/Size Round with Flat Top, 2.40mm Voltage - Forward (Vf) (Typ) 1.85V Red, 1.9V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 640nm Red, 585nm Yellow Wavelength - Peak - Features - Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Manufacturer	Bivar Inc.
Package 4-PLCC Series - Color Red, Yellow Configuration Independent Lens Color Colorless Lens Transparency Clear Millicandela Rating 36mcd Red, 16mcd Yellow Lens Style/Size Round with Flat Top, 2.40mm Voltage - Forward (Vf) (Typ) 1.85V Red, 1.9V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 640nm Red, 585nm Yellow Wavelength - Peak - Features - Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Category	Optoelectronics
Series - Color Red, Yellow Configuration Independent Lens Color Colorless Lens Transparency Clear Millicandela Rating 36mcd Red, 16mcd Yellow Lens Style/Size Round with Flat Top, 2.40mm Voltage - Forward (Vf) (Typ) 1.85V Red, 1.9V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 640nm Red, 585nm Yellow Wavelength - Peak - Features - Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm		LED Indication - Discrete
ColorRed, YellowConfigurationIndependentLens ColorColorlessLens TransparencyClearMillicandela Rating36mcd Red, 16mcd YellowLens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.85V Red, 1.9V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle120°Mounting TypeSurface MountWavelength - Dominant640nm Red, 585nm YellowWavelength - Peak-Features-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.85mm	Package	4-PLCC
ConfigurationIndependentLens ColorColorlessLens TransparencyClearMillicandela Rating36mcd Red, 16mcd YellowLens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.85V Red, 1.9V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle120°Mounting TypeSurface MountWavelength - Dominant640nm Red, 585nm YellowWavelength - Peak-Features-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.85mm	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating36mcd Red, 16mcd YellowLens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.85V Red, 1.9V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle120°Mounting TypeSurface MountWavelength - Dominant640nm Red, 585nm YellowWavelength - Peak-Features-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.85mm	Color	Red, Yellow
Lens TransparencyClearMillicandela Rating36mcd Red, 16mcd YellowLens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.85V Red, 1.9V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle120°Mounting TypeSurface MountWavelength - Dominant640nm Red, 585nm YellowWavelength - Peak-Features-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.85mm	Configuration	Independent
Millicandela Rating Lens Style/Size Round with Flat Top, 2.40mm Voltage - Forward (Vf) (Typ) 1.85V Red, 1.9V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 640nm Red, 585nm Yellow Wavelength - Peak - Features - Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Lens Color	Colorless
Lens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.85V Red, 1.9V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle120°Mounting TypeSurface MountWavelength - Dominant640nm Red, 585nm YellowWavelength - Peak-Features-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.85mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) Current - Test 20mA Red, 20mA Yellow Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 640nm Red, 585nm Yellow Vavelength - Peak Features - Package / Case 4-PLCC Supplier Device Package Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Millicandela Rating	36mcd Red, 16mcd Yellow
Current - Test 20mA Red, 20mA Yellow Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 640nm Red, 585nm Yellow Wavelength - Peak - Features - Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Lens Style/Size	Round with Flat Top, 2.40mm
Viewing Angle120°Mounting TypeSurface MountWavelength - Dominant640nm Red, 585nm YellowWavelength - Peak-Features-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.85mm	Voltage - Forward (Vf) (Typ)	1.85V Red, 1.9V Yellow
Mounting Type Surface Mount Wavelength - Dominant 640nm Red, 585nm Yellow Wavelength - Peak - Features - Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Current - Test	20mA Red, 20mA Yellow
Wavelength - Dominant Wavelength - Peak Features - Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Viewing Angle	120°
Wavelength - Peak - Features - Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Mounting Type	Surface Mount
Features Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Wavelength - Dominant	640nm Red, 585nm Yellow
Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Wavelength - Peak	-
Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Features	-
Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.85mm	Package / Case	4-PLCC
Height (Max) 1.85mm	Supplier Device Package	4-PLCC
	Size / Dimension	3.20mm L x 2.80mm W
Report errors?	Height (Max)	1.85mm
		Report errors?

SMP4-BC-RY Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SMP4-BC-RY Payment Methods



















SMP4-BC-RY Shipping Methods













If you have any question about SMP4-BC-RY, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com