

SMS9RE3S6

SMS9RE3S6 Information

Man	Number ufacturer		6.5 %6
Categ	gory	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
Descr	ription	SMS VERTICAL BOARD MT.	- 121-F.G.
Packa	age	-	同時の重要
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	Request a Quote

E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SMS9RE3S6 Specifications

Manufacturer Part NumberSMS9RE3S6ManufacturerSouriauCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesSMSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions9		
CategoryConnectors, InterconnectsCategoryConnectors - Headers, Receptacles, Female SocketsPackage-SeriesSMSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or Cable	Manufacturer Part Number	SMS9RE3S6
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesSMSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or Cable	Manufacturer	Souriau
Package-SeriesSMSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or Cable	Category	Connectors, Interconnects
SeriesSMSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or Cable		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or Cable	Package	-
Contact TypeFemale SocketStyleBoard to Board or Cable	Series	SMS
Style Board to Board or Cable	Connector Type	Receptacle
	Contact Type	Female Socket
Number of Positions 9	Style	Board to Board or Cable
	Number of Positions	9
Number of Positions Loaded All	Number of Positions Loaded	All
Pitch - Mating 0.200" (5.08mm)	Pitch - Mating	0.200" (5.08mm)
Number of Rows 3	Number of Rows	3
Row Spacing - Mating 0.200" (5.08mm)	Row Spacing - Mating	0.200" (5.08mm)
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Solder	Termination	Solder
Fastening Type Locking Ramp	Fastening Type	Locking Ramp
Contact Finish - Mating Gold	Contact Finish - Mating	Gold
Contact Finish Thickness - Mating 29.5µin (0.75µm)	Contact Finish Thickness - Mating	29.5µin (0.75µm)
Insulation Color Black	Insulation Color	Black
Insulation Height 0.528" (13.40mm)	Insulation Height	0.528" (13.40mm)
Contact Length - Post 0.173" (4.40mm)	Contact Length - Post	0.173" (4.40mm)
Operating Temperature $-55^{\circ}C \sim 105^{\circ}C$	Operating Temperature	-55°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Gold	
Mated Stacking Heights	-	
Ingress Protection	IP40	
Features	Mounting Flange	
		Demont emens?

Report errors?

SMS9RE3S6 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about SMS9RE3S6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com