



SMX43C106KAN360 Information



For Reference Only

Part Number SMX43C106KAN360 Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 10UF 25V X7R 8-DIP

Package 8-DII

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SMX43C106KAN360 Specifications

Manufacturer Part Number SMX43C106KAN360 Manufacturer AVX Corporation Category Capacitors Package 8-DIP Series SMX Capacitance 10µF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R (VHT) Operating Temperature -55°C ~ 200°C Features Low ESL (Stacked), High Temperature Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style -		
Category Capacitors Package 8-DIP Series SMX Capacitance 10μF Tolerance ±10% Voltage - Rated 25 V Temperature Coefficient X7R (VHT) Operating Temperature -55°C ~ 200°C Features Low ESL (Stacked), High Temperature Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style -	Manufacturer Part Number	SMX43C106KAN360
Package 8-DIP Series SMX Capacitance 10μF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R (VHT) Operating Temperature -55°C ~ 200°C Features Low ESL (Stacked), High Temperature Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style -	Manufacturer	AVX Corporation
Package 8-DIP Series SMX Capacitance 10μF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R (VHT) Operating Temperature -55°C ~ 200°C Features Low ESL (Stacked), High Temperature Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style -	Category	Capacitors
Series SMX Capacitance 10µF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R (VHT) Operating Temperature -55°C ~ 200°C Features Low ESL (Stacked), High Temperature Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style -		Ceramic Capacitors
Capacitance 10μF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R (VHT) Operating Temperature -55°C ~ 200°C Features Low ESL (Stacked), High Temperature Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style -	Package	8-DIP
Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R (VHT) Operating Temperature -55°C ~ 200°C Features Low ESL (Stacked), High Temperature Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style -	Series	SMX
Voltage - Rated25VTemperature CoefficientX7R (VHT)Operating Temperature-55°C ~ 200°CFeaturesLow ESL (Stacked), High TemperatureRatings-ApplicationsSMPS FilteringFailure Rate-Mounting TypeThrough HolePackage / Case8-DIPSize / Dimension0.402" L x 0.441" W (10.20mm x 11.20mm)Height - Seated (Max)0.360" (9.14mm)Thickness (Max)-Lead Spacing0.400" (10.16mm)Lead Style-	Capacitance	10μF
Temperature Coefficient Operating Temperature -55°C ~ 200°C Features Low ESL (Stacked), High Temperature Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) - Lead Spacing Lead Style - X7R (VHT) A7R (VHT) A7	Tolerance	±10%
Operating Temperature-55°C ~ 200°CFeaturesLow ESL (Stacked), High TemperatureRatings-ApplicationsSMPS FilteringFailure Rate-Mounting TypeThrough HolePackage / Case8-DIPSize / Dimension0.402" L x 0.441" W (10.20mm x 11.20mm)Height - Seated (Max)0.360" (9.14mm)Thickness (Max)-Lead Spacing0.400" (10.16mm)Lead Style-	Voltage - Rated	25V
FeaturesLow ESL (Stacked), High TemperatureRatings-ApplicationsSMPS FilteringFailure Rate-Mounting TypeThrough HolePackage / Case8-DIPSize / Dimension0.402" L x 0.441" W (10.20mm x 11.20mm)Height - Seated (Max)0.360" (9.14mm)Thickness (Max)-Lead Spacing0.400" (10.16mm)Lead Style-	Temperature Coefficient	X7R (VHT)
Ratings - SMPS Filtering SMPS Filtering Failure Rate - Through Hole Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style - SMPS Filtering S	Operating Temperature	-55°C ~ 200°C
Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style	Features	Low ESL (Stacked), High Temperature
Failure Rate - Mounting Type Through Hole Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style -	Ratings	-
Mounting Type Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style	Applications	SMPS Filtering
Package / Case 8-DIP Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style -	Failure Rate	-
Size / Dimension 0.402" L x 0.441" W (10.20mm x 11.20mm) Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) 0.360" (9.14mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style -	Package / Case	8-DIP
Thickness (Max) Lead Spacing 0.400" (10.16mm) Lead Style -	Size / Dimension	0.402" L x 0.441" W (10.20mm x 11.20mm)
Lead Spacing 0.400" (10.16mm) Lead Style -	Height - Seated (Max)	0.360" (9.14mm)
Lead Style -	Thickness (Max)	-
·	Lead Spacing	0.400" (10.16mm)
Report errors?	Lead Style	-
		Report errors?

SMX43C106KAN360 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SMX43C106KAN360 Payment Methods



















SMX43C106KAN360 Shipping Methods













If you have any question about SMX43C106KAN360, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com