

SN74LVC2G07DBVRE4

SN74LVC2G07DBVRE4 Information

M C D	 SN74LVC2G07DBVRE4 Texas Instruments Integrated Circuits (ICs) Logic - Buffers, Drivers, Receivers, Transceivers IC BUFF/DVR DL NON-INV SOT23-6 SOT-23-6 For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SN74LVC2G07DBVRE4 Specifications

Manufacturer Part Number SN74LVC2G07DBVRE4 Manufacturer Texas Instruments Category Integrated Circuits (ICs) Logic - Buffers, Drivers, Receivers, Transceivers Sort-23-6 Package SOT-23-6 Series 74LVC Logic Type Buffer, Non-Inverting Number of Elements 2 Number of Bits per Element 1 Input Type Open Drain Current - Output High, Low -, 32mA Voltage - Supply 1.65 V ~ 5.5 V Operating Temperature 40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6		
CategoryIntegrated Circuits (ICs)Logic - Buffers, Drivers, Receivers, TransceiversPackageSOT-23-6Series74LVCLogic TypeBuffer, Non-InvertingNumber of Elements2Number of Bits per Element1Input Type-Output TypeOpen DrainCurrent - Output High, Low.32mAVoltage - Supply1.65 V ~ 5.5 VOperating Temperature40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6	Manufacturer Part Number	SN74LVC2G07DBVRE4
Logic - Buffers, Drivers, Receivers, TransceiversPackageSOT-23-6Series74LVCLogic TypeBuffer, Non-InvertingNumber of Elements2Number of Bits per Element1Input Type-Output TypeOpen DrainCurrent - Output High, Low-, 32mAVoltage - Supply1.65 V ~ 5.5 VOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6	Manufacturer	Texas Instruments
PackageSOT-23-6Series74LVCLogic TypeBuffer, Non-InvertingNumber of Elements2Number of Bits per Element1Input Type-Output TypeOpen DrainCurrent - Output High, Low., 32mAVoltage - Supply1.65 V ~ 5.5 VOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6	Category	Integrated Circuits (ICs)
Series74LVCLogic TypeBuffer, Non-InvertingNumber of Elements2Number of Bits per Element1Input Type-Output TypeOpen DrainCurrent - Output High, Low-, 32mAVoltage - Supply1.65 V ~ 5.5 VOperating TemperatureSurface MountMounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6		Logic - Buffers, Drivers, Receivers, Transceivers
Logic TypeBuffer, Non-InvertingNumber of Elements2Number of Bits per Element1Input Type-Output TypeOpen DrainCurrent - Output High, Low-, 32mAVoltage - Supply1.65 V ~ 5.5 VOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6	Package	SOT-23-6
Number of Elements2Number of Bits per Element1Input Type-Output TypeOpen DrainCurrent - Output High, Low-, 32mAVoltage - Supply1.65 V ~ 5.5 VOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6	Series	74LVC
Number of Bits per Element1Input Type-Output TypeOpen DrainCurrent - Output High, Low-, 32mAVoltage - Supply1.65 V ~ 5.5 VOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6	Logic Type	Buffer, Non-Inverting
Input Type - Output Type Open Drain Current - Output High, Low -, 32mA Voltage - Supply 1.65 V ~ 5.5 V Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Supplier Device Package SOT-23-6	Number of Elements	2
Output TypeOpen DrainCurrent - Output High, Low-, 32mAVoltage - Supply1.65 V ~ 5.5 VOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6	Number of Bits per Element	1
Current - Output High, Low-, 32mAVoltage - Supply1.65 V ~ 5.5 VOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6	Input Type	-
Voltage - Supply1.65 V ~ 5.5 VOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6	Output Type	Open Drain
Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6	Current - Output High, Low	-, 32mA
Mounting TypeSurface MountPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6	Voltage - Supply	1.65 V ~ 5.5 V
Package / CaseSOT-23-6Supplier Device PackageSOT-23-6	Operating Temperature	-40°C ~ 125°C (TA)
Supplier Device Package SOT-23-6	Mounting Type	Surface Mount
	Package / Case	SOT-23-6
	Supplier Device Package	SOT-23-6
Report errors?		Report errors?

SN74LVC2G07DBVRE4 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SN74LVC2G07DBVRE4 Payment Methods





If you have any question about SN74LVC2G07DBVRE4, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com