

SN75ALS176BDR

SN75ALS176BDR Information

With Intener.com	Part Number Manufacturer Category Description Package	SN75ALS176BDR Texas Instruments Integrated Circuits (ICs) Interface - Drivers, Receivers, Transceivers IC DIFF BUS TXRX 8-SOIC 8-SOIC (0.154", 3.90mm Width) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SN75ALS176BDR Specifications

Manufacturer Texas Instruments Category Integrated Circuits (ICs) Interface - Drivers, Receivers, Transceivers Interface - Drivers, Receivers, Transceivers Package 8-SOIC (0.154", 3.90mm Width) Series - Protocol Transceiver Number of Drivers/Receivers RS422, RS485 Number of Drivers/Receivers 1/1 Duplex 60mV Cata Rate - Voltage - Supply 4.75 V ~ 5.25 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)		
CategoryIntegrated Circuits (ICs)Interface - Drivers, Receivers, TransceiversPackage8-SOIC (0.154", 3.90mm Width)Series-FypeTransceiverProtocolRS422, RS485Number of Drivers/Receivers1/1Duplex60mVReceiver Hysteresis60mVData Rate-Voltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSerIece MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Manufacturer Part Number	SN75ALS176BDR
Interface - Drivers, Receivers, TransceiversPackage8-SOIC (0.154", 3.90mm Width)Series-TypeTransceiverProtocolRS422, RS485Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis60mVData Rate-Voltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Manufacturer	Texas Instruments
Package 8-SOIC (0.154", 3.90mm Width) Series - Type Transceiver Protocol RS422, RS485 Number of Drivers/Receivers 1/1 Duplex Half Receiver Hysteresis 60mV Outage - Supply 4.75 V ~ 5.25 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Category	Integrated Circuits (ICs)
Series-FypeTransceiverProtocolRS422, RS485Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis60mVData Rate-Voltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)		Interface - Drivers, Receivers, Transceivers
TypeTransceiverProtocolRS422, RS485Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis60mVData Rate-Voltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Package	8-SOIC (0.154", 3.90mm Width)
ProtocolRS422, RS485Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis60mVData Rate-Voltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Series	-
Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis60mVData Rate-Voltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Туре	Transceiver
DuplexHalfReceiver Hysteresis60mVData Rate-Voltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Protocol	RS422, RS485
Receiver Hysteresis60mVData Rate-Voltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Number of Drivers/Receivers	1/1
Data Rate-Voltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Duplex	Half
Woltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Receiver Hysteresis	60mV
Operating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Data Rate	-
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Voltage - Supply	4.75 V ~ 5.25 V
Package / Case 8-SOIC (0.154", 3.90mm Width)	Operating Temperature	0° C ~ 70° C
-	Mounting Type	Surface Mount
Solic Solice Paskage 8 SOLC	Package / Case	8-SOIC (0.154", 3.90mm Width)
ouppiler Device Fackage 8-SOIC	Supplier Device Package	8-SOIC
Report errors?		Report errors?

SN75ALS176BDR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SN75ALS176BDR Payment Methods



If you have any question about SN75ALS176BDR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com