



SNDBS400B12 Information

Heisener.com

Part Number SNDBS400B12 Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description VALUED ADDED PS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SNDBS400B12 Specifications

Manufacturer Part Number SNDBS400B12 Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series SNDBS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 34A Power (Watts) 408W Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm) Report errors?			
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series SNDBS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 34A Power (Watts) 408W Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Manufacturer Part Number	SNDBS400B12	
Package - Series SNDBS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 34A Power (Watts) 408W Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Manufacturer	Cosel USA, Inc.	
Package - Series SNDBS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 34A Power (Watts) 408W Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series SNDBS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 34A Power (Watts) 408W Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)		DC DC Converters	
Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 34A Power (Watts) 408W Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Package	-	
Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 34A Power (Watts) 408W Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Series	SNDBS	
Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 34A Power (Watts) 408W Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Type	Open Frame	
Number of Outputs1Voltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)34APower (Watts)408WApplicationsITE (Commercial)Operating Temperature-20°C ~ 80°C (With Derating)Efficiency87%Mounting TypeChassis MountPackage / Case-Size / Dimension8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Voltage - Input (Min)	200V	
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 34A Power (Watts) 408W Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Voltage - Input (Max)	400V	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency Mounting Type Chassis Mount Package / Case Size / Dimension - Current - Output (Max)	Number of Outputs	1	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Size / Dimension - Current - Output (Max) 34A - 408W 408W ITE (Commercial) -20°C ~ 80°C (With Derating) Efficiency 87% Chassis Mount 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Voltage - Output 1	12V	
Voltage - Output 4 Current - Output (Max) 34A Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case Size / Dimension	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case Size / Dimension 34A 408W Commercial -20°C ~ 80°C (With Derating)	Voltage - Output 3	-	
Power (Watts) 408W Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Current - Output (Max)	34A	
Operating Temperature -20°C ~ 80°C (With Derating) Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Power (Watts)	408W	
Efficiency 87% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Applications	ITE (Commercial)	
Mounting Type Chassis Mount Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Operating Temperature	-20°C ~ 80°C (With Derating)	
Package / Case - Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Efficiency	87%	
Size / Dimension 8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	Mounting Type	Chassis Mount	
	Package / Case	-	
Report errors?	Size / Dimension	8.75" L x 3.51" W x 1.75" H (222.3mm x 89.2mm x 44.5mm)	
		Report error	rs?

SNDBS400B12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SNDBS400B12 Payment Methods



















SNDBS400B12 Shipping Methods













If you have any question about SNDBS400B12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com