



SNDHS100B03 Information

Heisener.com

Part Number SNDHS100B03 Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description VALUED ADDED PS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SNDHS100B03 Specifications

Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount			
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Manufacturer Part Number	SNDHS100B03	
Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Manufacturer	Cosel USA, Inc.	
Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)		DC DC Converters	
Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Package	-	
Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Series	SNDHS	
Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Type	Open Frame	
Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Voltage - Input (Min)	200V	
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency Mounting Type Chassis Mount Package / Case Size / Dimension 3.3V 3.3V 3.3V 3.3V 3.3V 4.3V 5.0V Chassis Mount - Current - Output (Max) - Chassis Mount -20°C ~ 95°C (With Derating) Chassis Mount Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Voltage - Input (Max)	400V	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency Mounting Type Chassis Mount Package / Case Size / Dimension - Current - Output (Max) - Current - Output (Max) - Commercial) - Commercial -	Number of Outputs	1	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Operating Temperature -20°C ~ 95°C (With Derating) Efficiency Mounting Type Chassis Mount Package / Case Size / Dimension - Current - Output (Max) - Commercial (Ma	Voltage - Output 1	3.3V	
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case Size / Dimension - 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Voltage - Output 2	-	
Current - Output (Max) 20A Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case Size / Dimension 20A 66W Commercial -20°C ~ 95°C (With Derating)	Voltage - Output 3	-	
Power (Watts) 66W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Current - Output (Max)	20A	
Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Power (Watts)	66W	
Efficiency 78% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Applications	ITE (Commercial)	
Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Operating Temperature	-20°C ~ 95°C (With Derating)	
Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Efficiency	78%	
Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Mounting Type	Chassis Mount	
	Package / Case	-	
Report errors?	Size / Dimension	5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	
		F	Report errors?

SNDHS100B03 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SNDHS100B03 Payment Methods





















SNDHS100B03 Shipping Methods













If you have any question about SNDHS100B03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com