



SNDHS100B15 Information

Heisener.com

Part Number SNDHS100B15 Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description VALUED ADDED PS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SNDHS100B15 Specifications

Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount			
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Manufacturer Part Number	SNDHS100B15	
Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Manufacturer	Cosel USA, Inc.	
Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series SNDHS Type Open Frame Voltage - Input (Min) 200V Number of Outputs 400V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)		DC DC Converters	
Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Package	-	
Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Series	SNDHS	
Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Type	Open Frame	
Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Voltage - Input (Min)	200V	
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency Mounting Type Chassis Mount Package / Case Size / Dimension 15V 15V 15V 16V 16V 17V 17V 17V 17V 17V 17	Voltage - Input (Max)	400V	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency Mounting Type Chassis Mount Package / Case Size / Dimension - Curpent - Output (Max) - Curpent - Ou	Number of Outputs	1	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Size / Dimension - Output (Max) - Conder (M	Voltage - Output 1	15V	
Voltage - Output 4 Current - Output (Max) 6.7A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case Size / Dimension	Voltage - Output 2	-	
Current - Output (Max) 6.7A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case Size / Dimension 6.7A 6.7A 6.7A Commercial FITE (Commercial) -20°C ~ 95°C (With Derating) -20°C ~ 95°C (With Derating) 5.00° L x 2.42° W x 1.75° H (127.0mm x 61.5mm x 44.5mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 101W Commercial Commerci	Voltage - Output 4	-	
Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Current - Output (Max)	6.7A	
Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Power (Watts)	101W	
Efficiency 85% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Applications	ITE (Commercial)	
Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Operating Temperature	-20°C ~ 95°C (With Derating)	
Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Efficiency	85%	
Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Mounting Type	Chassis Mount	
	Package / Case	-	
Report errors?	Size / Dimension	5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	
		Report	errors?

SNDHS100B15 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SNDHS100B15 Payment Methods





















SNDHS100B15 Shipping Methods













If you have any question about SNDHS100B15, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com