



### **SNDHS100B24 Information**

Heisener.com

Part Number SNDHS100B24 Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

**Description** VALUED ADDED PS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **SNDHS100B24 Specifications**

Manufacturer         Cosel USA, Inc.           Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         -           Series         SNDHS           Type         Open Frame           Voltage - Input (Min)         200V           Voltage - Input (Max)         400V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         4.2A           Power (Watts)         101W           Applications         ITE (Commercial)           Operating Temperature         -20°C ~ 95°C (With Derating)           Efficiency         85%           Mounting Type         Chassis Mount		
Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         -           Series         SNDHS           Type         Open Frame           Voltage - Input (Min)         200V           Voltage - Input (Max)         400V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         4.2A           Power (Watts)         101W           Applications         ITE (Commercial)           Operating Temperature         -20°C ~ 95°C (With Derating)           Efficiency         85%           Mounting Type         Chassis Mount	Manufacturer Part Number	SNDHS100B24
DC DC Converters	Manufacturer	Cosel USA, Inc.
Package - Series SNDHS Type Open Frame  Voltage - Input (Min) 200V  Voltage - Input (Max) 400V  Number of Outputs 1  Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  Current - Output (Max) 4.2A  Power (Watts) 101W  Applications ITE (Commercial)  Operating Temperature 25%  Mounting Type Chassis Mount	Category	Power Supplies - External/Internal (Off-Board)
Series         SNDHS           Type         Open Frame           Voltage - Input (Min)         200V           Voltage - Input (Max)         400V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         4.2A           Power (Watts)         101W           Applications         ITE (Commercial)           Operating Temperature         -20°C ~ 95°C (With Derating)           Efficiency         85%           Mounting Type         Chassis Mount		DC DC Converters
Type Open Frame  Voltage - Input (Min) 200V  Voltage - Input (Max) 400V  Number of Outputs 1  Voltage - Output 1 24V  Voltage - Output 2 -  Voltage - Output 3 -  Voltage - Output 4 -  Current - Output (Max) 4.2A  Power (Watts) 101W  Applications ITE (Commercial)  Operating Temperature -20°C ~ 95°C (With Derating)  Efficiency 85%  Mounting Type Chassis Mount	Package	-
Voltage - Input (Min)       200V         Voltage - Input (Max)       400V         Number of Outputs       1         Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       4.2A         Power (Watts)       101W         Applications       ITE (Commercial)         Operating Temperature       -20°C ~ 95°C (With Derating)         Efficiency       85%         Mounting Type       Chassis Mount	Series	SNDHS
Voltage - Input (Max)  Number of Outputs  1  Voltage - Output 1  24V  Voltage - Output 2  - Voltage - Output 3  - Current - Output (Max)  Applications  Operating Temperature  Efficiency  Mounting Type  400V  101V  101V  4.2A  101W  10	Type	Open Frame
Number of Outputs  Voltage - Output 1  24V  Voltage - Output 2  - Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  Operating Temperature  Efficiency  Mounting Type  1  24V  -  - Current - Output 2	Voltage - Input (Min)	200V
Voltage - Output 1  Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  -20°C ~ 95°C (With Derating)  Efficiency  Mounting Type  Chassis Mount	Voltage - Input (Max)	400V
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4	Number of Outputs	1
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  Operating Temperature  Efficiency  Mounting Type  - Output 3  - Applications  - Current - Output (Max)  - Applications  - Commercial (With Derating)  - Chassis Mount	Voltage - Output 1	24V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  -20°C ~ 95°C (With Derating)  Efficiency  Mounting Type  Chassis Mount	Voltage - Output 2	-
Current - Output (Max)  4.2A  Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  -20°C ~ 95°C (With Derating)  Efficiency  85%  Mounting Type  Chassis Mount	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  -20°C ~ 95°C (With Derating)  Efficiency  85%  Mounting Type  Chassis Mount	Voltage - Output 4	-
Applications ITE (Commercial)  Operating Temperature -20°C ~ 95°C (With Derating)  Efficiency 85%  Mounting Type Chassis Mount	Current - Output (Max)	4.2A
Operating Temperature -20°C ~ 95°C (With Derating)  Efficiency 85%  Mounting Type Chassis Mount	Power (Watts)	101W
Efficiency 85% Mounting Type Chassis Mount	Applications	ITE (Commercial)
Mounting Type Chassis Mount	Operating Temperature	$-20^{\circ}$ C ~ $95^{\circ}$ C (With Derating)
	Efficiency	85%
	Mounting Type	Chassis Mount
Package / Case -	Package / Case	-
Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Size / Dimension	5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)
Report er		Report errors?

### **SNDHS100B24 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **SNDHS100B24 Payment Methods**



















### **SNDHS100B24 Shipping Methods**













If you have any question about SNDHS100B24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com