



SNDHS100B28 Information

Heisener.com

Part Number SNDHS100B28 Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description VALUED ADDED PS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SNDHS100B28 Specifications

Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.6A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating)	•	
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Operating Temperature Power (Watts) IDC DC Converters Internal (Off-Board) DC DC Converters - External/Internal (Off-Board) DC DC Converters - Substitution Supplies - External/Internal (Off-Board) DC DC Converters - Supplies - External/Internal (Off-Board) DC DC Converters - Supplies - External/Internal (Off-Board) - DC DC Converters - Supplies - External/Internal (Off-Board) - DC DC Converters - Supplies - External/Internal (Off-Board) - DC DC Converters - Supplies - External/Internal (Off-Board) - S	Manufacturer Part Number	SNDHS100B28
DC DC Converters	Manufacturer	Cosel USA, Inc.
Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.6A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating)	Category	Power Supplies - External/Internal (Off-Board)
Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.6A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating)		DC DC Converters
Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.6A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating)	Package	-
Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.6A Power (Watts) 101W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating)	Series	SNDHS
Voltage - Input (Max) Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Operating Temperature 400V 400V	Type	Open Frame
Number of Outputs Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Operating Temperature 1 28V - Voltage - Output 2 - Current - Output (Max) 101W 101W	Voltage - Input (Min)	200V
Voltage - Output 2 Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Operating Temperature 28V - 101W 28V 101W 200C ~ 95°C (With Derating)	Voltage - Input (Max)	400V
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) -20°C ~ 95°C (With Derating)	Number of Outputs	1
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Operating Temperature - Output 3 - Output 4 - Output (Max) 3.6A 101W ITE (Commercial) -20°C ~ 95°C (With Derating)	Voltage - Output 1	28V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications Operating Temperature - 20°C ~ 95°C (With Derating)	Voltage - Output 2	-
Current - Output (Max) 3.6A Power (Watts) Applications Operating Temperature 3.6A 101W ITE (Commercial) -20°C ~ 95°C (With Derating)	Voltage - Output 3	-
Power (Watts) Applications Operating Temperature 101W ITE (Commercial) -20°C ~ 95°C (With Derating)	Voltage - Output 4	-
Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating)	Current - Output (Max)	3.6A
Operating Temperature -20°C ~ 95°C (With Derating)	Power (Watts)	101W
	Applications	ITE (Commercial)
Efficiency 85%	Operating Temperature	-20° C ~ 95° C (With Derating)
	Efficiency	85%
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Package / Case -	Package / Case	-
Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Size / Dimension	5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)
Report en		Report errors?

SNDHS100B28 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SNDHS100B28 Payment Methods





















SNDHS100B28 Shipping Methods













If you have any question about SNDHS100B28, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com