



SNDHS250B28 Information

Heisener.com

Part Number SNDHS250B28 Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description VALUED ADDED PS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SNDHS250B28 Specifications

Manufacturer Part Number SNDHS250B28 Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 9A Power (Watts) 252W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)			
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 9A Power (Watts) 252W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Manufacturer Part Number	SNDHS250B28	
Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 9A Power (Watts) 252W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Manufacturer	Cosel USA, Inc.	
Package - Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 9A Power (Watts) 252W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series SNDHS Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 9A Power (Watts) 252W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)		DC DC Converters	
Type Open Frame Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 9A Power (Watts) 252W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Package	-	
Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 9A Power (Watts) 252W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Series	SNDHS	
Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 9A Power (Watts) 252W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Type	Open Frame	
Number of Outputs 1 Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 9A Power (Watts) 252W Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Voltage - Input (Min)	200V	
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature Efficiency 86% Mounting Type Chassis Mount Package / Case Size / Dimension 28V	Voltage - Input (Max)	400V	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Size / Dimension - Output 2 - Current - Output (Max) 9A - Current - Output (Max) 9A Power (Watts) 1TE (Commercial) - Coo ~ 95 °C (With Derating) 86% Mounting Type Chassis Mount 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Number of Outputs	1	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case Size / Dimension - Size / Dimension - Current - Output 4 - Current - Output (Max) 9A - Commercial - Commercial - Commercial - Size / With Derating - Chassis Mount - Size / Dimension	Voltage - Output 1	28V	
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case Size / Dimension	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 9A 252W Commercial -20°C ~ 95°C (With Derating)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Current - Output (Max)	9A	
Operating Temperature -20°C ~ 95°C (With Derating) Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension -20°C ~ 95°C (With Derating) 86% Kith Derating 100 100 100 100 100 100 100 1	Power (Watts)	252W	
Efficiency 86% Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Applications	ITE (Commercial)	
Mounting Type Chassis Mount Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Operating Temperature	-20°C ~ 95°C (With Derating)	
Package / Case - Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Efficiency	86%	
Size / Dimension 5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	Mounting Type	Chassis Mount	
	Package / Case	-	
Report errors?	Size / Dimension	5.00" L x 2.42" W x 1.75" H (127.0mm x 61.5mm x 44.5mm)	
			Report errors?

SNDHS250B28 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SNDHS250B28 Payment Methods





















SNDHS250B28 Shipping Methods













If you have any question about SNDHS250B28, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com