



### **SNLM-P-S25-25S-GY Information**

Heisener.com

Part Number SNLM-P-S25-25S-GY Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN STR PLUG SET SCRW PIN GRY

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **SNLM-P-S25-25S-GY Specifications**

Manufacturer Part Number       SNLM-P-S25-25S-GY         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       Snaplock         Connector Type       Plug, Male Pins         Number of Positions       1         Shell Size - Insert       -         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Set Screw         Fastening Type       Bayonet Lock         Orientation       -         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Thermoplastic         Contact Finish       Silver         Features       Slide Lock         Voltage - Rated       1000VAC, 1500VDC         Current Rating       250A		
CategoryConnectors, InterconnectsPackage-SeriesSnaplockConnector TypePlug, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesSlide LockVoltage - Rated1000VAC, 1500VDCCurrent Rating250A	Manufacturer Part Number	SNLM-P-S25-25S-GY
Package-SeriesSnaplockConnector TypePlug, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesSlide LockVoltage - Rated1000VAC, 1500VDCCurrent Rating250A	Manufacturer	ITT Cannon, LLC
Package-SeriesSnaplockConnector TypePlug, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesSlide LockVoltage - Rated1000VAC, 1500VDCCurrent Rating250A	Category	Connectors, Interconnects
SeriesSnaplockConnector TypePlug, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesSlide LockVoltage - Rated1000VAC, 1500VDCCurrent Rating250A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesSlide LockVoltage - Rated1000VAC, 1500VDCCurrent Rating250A	Package	-
Number of Positions  Shell Size - Insert  - Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Set Screw Fastening Type Bayonet Lock  Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic  Contact Finish Silver  Features Slide Lock  Voltage - Rated 1000VAC, 1500VDC  Current Rating  250A	Series	Snaplock
Shell Size - Insert Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Set Screw Fastening Type Bayonet Lock Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Set Screw  Fastening Type Bayonet Lock Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock  Voltage - Rated 1000VAC, 1500VDC Current Rating  -  Contact Finish Contact Finish Silver	Number of Positions	1
Mounting Type Free Hanging (In-Line)  Termination Set Screw  Fastening Type Bayonet Lock  Orientation -  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Thermoplastic  Contact Finish Silver  Features Slide Lock  Voltage - Rated 1000VAC, 1500VDC  Current Rating 250A	Shell Size - Insert	-
Termination Set Screw Fastening Type Bayonet Lock Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A	Shell Size, MIL	-
Fastening Type  Orientation  Ingress Protection  Shell Material, Finish  Contact Finish  Features  Voltage - Rated  Current Rating  Bayonet Lock  Bayonet Lock  IP67 - Dust Tight, Waterproof  Thermoplastic  Silver  Silver  Slide Lock  1000VAC, 1500VDC  250A	Mounting Type	Free Hanging (In-Line)
Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A	Termination	Set Screw
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver  Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A	Orientation	-
Contact Finish Silver  Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A	Shell Material, Finish	Thermoplastic
Voltage - Rated 1000VAC, 1500VDC Current Rating 250A	Contact Finish	Silver
Current Rating 250A	Features	Slide Lock
-	Voltage - Rated	1000VAC, 1500VDC
Report errors?	Current Rating	250A
		Report errors?

### **SNLM-P-S25-25S-GY Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **SNLM-P-S25-25S-GY Payment Methods**



















# **SNLM-P-S25-25S-GY Shipping Methods**













If you have any question about SNLM-P-S25-25S-GY, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com