



SNLM-P-S35-25S-BL Information

Heisener.com

Part NumberSNLM-P-S35-25S-BLManufacturerITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN STR PLUG SET SCRW PIN BLU

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SNLM-P-S35-25S-BL Specifications

| Manufacturer Part Number SNLM-P-S35-25S-BL Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series Snaplock Connector Type Plug, Male Pins Number of Positions 1 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Set Screw Fastening Type Bayonet Lock Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A | | |
|---|--------------------------|-------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesSnaplockConnector TypePlug, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesSlide LockVoltage - Rated1000VAC, 1500VDCCurrent Rating250A | Manufacturer Part Number | SNLM-P-S35-25S-BL |
| Package-SeriesSnaplockConnector TypePlug, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesSlide LockVoltage - Rated1000VAC, 1500VDCCurrent Rating250A | Manufacturer | ITT Cannon, LLC |
| Package-SeriesSnaplockConnector TypePlug, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesSlide LockVoltage - Rated1000VAC, 1500VDCCurrent Rating250A | Category | Connectors, Interconnects |
| SeriesSnaplockConnector TypePlug, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesSlide LockVoltage - Rated1000VAC, 1500VDCCurrent Rating250A | | Circular Connectors |
| Connector TypePlug, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesSlide LockVoltage - Rated1000VAC, 1500VDCCurrent Rating250A | Package | - |
| Number of Positions Shell Size - Insert - Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Set Screw Fastening Type Bayonet Lock Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A | Series | Snaplock |
| Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Set Screw Fastening Type Bayonet Lock Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating | Connector Type | Plug, Male Pins |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Set Screw Fastening Type Bayonet Lock Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating - Contact Finish Contact Finish Silver | Number of Positions | 1 |
| Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesSlide LockVoltage - Rated1000VAC, 1500VDCCurrent Rating250A | Shell Size - Insert | - |
| Termination Set Screw Fastening Type Bayonet Lock Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A | Shell Size, MIL | - |
| Fastening Type Orientation Ingress Protection Shell Material, Finish Contact Finish Features Voltage - Rated Current Rating Easyonet Lock Bayonet Lock IP67 - Dust Tight, Waterproof Thermoplastic Silver Silver Slide Lock Voltage - Rated 1000VAC, 1500VDC 250A | Mounting Type | Free Hanging (In-Line) |
| Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A | Termination | Set Screw |
| Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A | Orientation | - |
| Contact Finish Silver Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A | Ingress Protection | IP67 - Dust Tight, Waterproof |
| Features Slide Lock Voltage - Rated 1000VAC, 1500VDC Current Rating 250A | Shell Material, Finish | Thermoplastic |
| Voltage - Rated 1000VAC, 1500VDC Current Rating 250A | Contact Finish | Silver |
| Current Rating 250A | Features | Slide Lock |
| - | Voltage - Rated | 1000VAC, 1500VDC |
| Report errors? | Current Rating | 250A |
| | | Report errors? |

SNLM-P-S35-25S-BL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SNLM-P-S35-25S-BL Payment Methods



















SNLM-P-S35-25S-BL Shipping Methods













If you have any question about SNLM-P-S35-25S-BL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com