



SP00CE-24-61P(SR) Information

Heisener.com

Part Number SP00CE-24-61P(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 61POS WALL MNT PIN

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP00CE-24-61P(SR) Specifications

Manufacturer Part Number SP00CE-24-61P(SR) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated Connectors, Interconnects Circular Connectors Alluminum, Anodic Coating (Alumilite) Contact Fastend Convertible Contact Finish Gold Voltage - Rated	Manufacturer Part Number	SP00CE-24-61P(SR)
Circular Connectors Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated MIL-DTL-26482 Series I, SP MIL - NIL-DTL-26482 Series I, SP MIL-DTL-26482	Manufacturer	Amphenol Industrial Operations
Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Characteristics Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated		Circular Connectors
Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated 600VAC	Package	-
Number of Positions Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Strain Relief Voltage - Rated 24-61	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Strain Relief Voltage - Rated	Number of Positions	61
Mounting Type Panel Mount, Flange Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated Orientation N (Normal) Environment Resistant Aluminum, Anodic Coating (Alumilite) Gold Features Orientation N (Normal) Environment Resistant Aluminum, Anodic Coating (Alumilite) Orientation Orientation N (Normal) Environment Resistant Aluminum, Anodic Coating (Alumilite) Orientation Orientation Orientation N (Normal) Environment Resistant Orientation Or	Shell Size - Insert	24-61
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Aluminum, Anodic Coating (Alumilite) Gold Footometrial, Finish Footometrial, Finish Gold Footometrial, Finish Foo	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 600VAC	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 600VAC	Contact Finish	Gold
-	Features	Strain Relief
Current Rating 7.5A	Voltage - Rated	600VAC
	Current Rating	7.5A
Report errors?		Report errors?

SP00CE-24-61P(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP00CE-24-61P(SR) Payment Methods



















SP00CE-24-61P(SR) Shipping Methods













If you have any question about SP00CE-24-61P(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com