



### SP00E-14-19P Information

Heisener.com

Part Number SP00E-14-19P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 19POS WALL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **SP00E-14-19P Specifications**

Manufacturer Part NumberSP00E-14-19PManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert 14-19 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Manufacturer Part Number	SP00E-14-19P
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions  Shell Size - Insert  14-19  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Gold  Features  Voltage - Rated  Current Rating  7.5A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated Current Rating 7.5A	Number of Positions	19
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	14-19
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC  Current Rating  7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection  Environment Resistant  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Gold  Features  Voltage - Rated  Current Rating  Environment Resistant  Aluminum, Anodic Coating (Alumilite)  Gold  7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Anodic Coating (Alumilite) Gold	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

### SP00E-14-19P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **SP00E-14-19P Payment Methods**





















### **SP00E-14-19P Shipping Methods**













If you have any question about SP00E-14-19P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com