

SP00P-12-8P(375) Information

Heisener.com

Part Number SP00P-12-8P(375)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 8POS WALL MNT PIN

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP00P-12-8P(375) Specifications

Manufacturer Part Number SP00P-12-8P(375) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 12-8 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish - Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	SP00P-12-8P(375)
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish - Contact Finish Features Potted Voltage - Rated Current Rating - 7.5A	Number of Positions	8
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	12-8
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish - Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish - Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection - Shell Material, Finish - Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection - Shell Material, Finish - Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Features Potted Voltage - Rated Current Rating 7.5A	Orientation	N (Normal)
Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	-
Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	-
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	-
Current Rating 7.5A	Features	Potted
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

SP00P-12-8P(375) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP00P-12-8P(375) Payment Methods





















SP00P-12-8P(375) Shipping Methods













If you have any question about SP00P-12-8P(375), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com