

SP00P-14-12P(375) Information

Heisener.com

Part Number SP00P-14-12P(375)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 12POS WALL MNT PIN

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP00P-14-12P(375) Specifications

Manufacturer Part Number SP00P-14-12P(375) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish - Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer Part Number	SP00P-14-12P(375)
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Package	-
Number of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish - Contact Finish Features Potted Voltage - Rated Current Rating - Tanala Mount, Flange Panel Moun	Number of Positions	12
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-FeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Shell Size - Insert	14-12
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish - Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish - Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection - Shell Material, Finish - Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Termination	Solder Cup
Ingress Protection - Shell Material, Finish - Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Features Potted Voltage - Rated Current Rating 7.5A, 13A	Orientation	N (Normal)
Contact Finish - Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Ingress Protection	-
Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Material, Finish	-
Voltage - Rated 600VAC Current Rating 7.5A, 13A	Contact Finish	-
Current Rating 7.5A, 13A	Features	Potted
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A, 13A
•		Report errors?

SP00P-14-12P(375) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP00P-14-12P(375) Payment Methods



















SP00P-14-12P(375) Shipping Methods













If you have any question about SP00P-14-12P(375), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com