

### SP00SE-14-19S(003) Information

Heisener.com

Part Number SP00SE-14-19S(003)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 19POS WALL MNT SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SP00SE-14-19S(003) Specifications

| Manufacturer Part Number       SP00SE-14-19S(003)         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-26482 Series I, SP         Connector Type       Receptacle, Female Sockets         Number of Positions       19         Shell Size - Insert       14-19         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Olive Drab Cadmium Plated         Contact Finish       Gold         Features       -         Voltage - Rated       600VAC         Current Rating       7.5A         Report errors? |                          |                                     |
|---|--------------------------|-------------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Female SocketsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A   | Manufacturer Part Number | SP00SE-14-19S(003)                  |
| Package-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Female SocketsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A  | Manufacturer             | Amphenol Industrial Operations      |
| Package-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Female SocketsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A  | Category                 | Connectors, Interconnects           |
| Series Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 14-19 Shell Size, MIL   |                          | Circular Connectors                 |
| Connector TypeReceptacle, Female SocketsNumber of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A  | Package                  | -                                   |
| Number of Positions19Shell Size - Insert14-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A  | Series                   | MIL-DTL-26482 Series I, SP          |
| Shell Size - Insert Shell Size, MIL   | Connector Type           | Receptacle, Female Sockets          |
| Shell Size, MIL  Mounting Type Panel Mount, Flange  Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A   | Number of Positions      | 19                                  |
| Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A   | Shell Size - Insert      | 14-19                               |
| Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A  | Shell Size, MIL          | -                                   |
| Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC  Current Rating  7.5A   | Mounting Type            | Panel Mount, Flange                 |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A  | Termination              | Crimp                               |
| Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold  Features -  Voltage - Rated 600VAC  Current Rating 7.5A  | Fastening Type           | Bayonet Lock                        |
| Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  600VAC  7.5A  | Orientation              | N (Normal)                          |
| Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A   | Ingress Protection       | Environment Resistant               |
| Features - Voltage - Rated 600VAC Current Rating 7.5A   | Shell Material, Finish   | Aluminum, Olive Drab Cadmium Plated |
| Voltage - Rated 600VAC Current Rating 7.5A  | Contact Finish           | Gold                                |
| Current Rating 7.5A   | Features                 | -                                   |
|   | Voltage - Rated          | 600VAC                              |
| Report errors?  | Current Rating           | 7.5A                                |
|   |                          | Report errors?                      |

### SP00SE-14-19S(003) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SP00SE-14-19S(003) Payment Methods



















# SP00SE-14-19S(003) Shipping Methods













If you have any question about SP00SE-14-19S(003), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com