

SP02E-14-12S Information

Heisener.com

Part Number SP02E-14-12S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 12POS BOX MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP02E-14-12S Specifications

Manufacturer Part Number SP02E-14-12S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Manufacturer Part Number	SP02E-14-12S
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A	Package	-
Number of Positions Shell Size - Insert 14-12 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated 600VAC Current Rating 7.5A, 13A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Voltage - Rated 600VAC Current Rating 7	Number of Positions	12
Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size - Insert	14-12
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Termination	Solder Cup
Ingress Protection Environment Resistant Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated Current Rating Environment Resistant Aluminum, Anodic Coating (Alumilite) Gold 7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Anodic Coating (Alumilite) Gold	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 600VAC Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A, 13A
		Report errors?

SP02E-14-12S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP02E-14-12S Payment Methods





















SP02E-14-12S Shipping Methods













If you have any question about SP02E-14-12S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com