

# SP02E-22-55P Information

Heisener.com

Part Number SP02E-22-55P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 55POS BOX MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SP02E-22-55P Specifications

Manufacturer Part NumberSP02E-22-55PManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions55Shell Size - Insert22-55Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5AReport errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Manufacturer Part Number	SP02E-22-55P
Circular Connectors  Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions55Shell Size - Insert22-55Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions  Shell Size - Insert  22-55  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC  Current Rating  7.5A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert  Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Gold  Features - Voltage - Rated 600VAC Current Rating 7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	55
Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Gold  Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size - Insert	22-55
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Anodic Coating (Alumilite)  Gold	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
-	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

#### SP02E-22-55P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# SP02E-22-55P Payment Methods



















## **SP02E-22-55P Shipping Methods**













If you have any question about SP02E-22-55P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com