

SP06A-16-26S Information

Heisener.com

Part Number SP06A-16-26S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 26POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP06A-16-26S Specifications

Manufacturer Part Number SP06A-16-26S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated Connectors, Interconnects Circular Connectors AllL NORD Plug, Female Sockets NIL - Plug, Female Sockets NIL-DTL-26482 Series I, SP Plug, Female Sockets NIL-DTL-26482 Series I, SP Plug, Female Sockets NIL-DTL-26482 Series I, SP Plug, Female Sockets Number of Positions All MIL-DTL-26482 Series I, SP Plug, Female Sockets Number of Positions All Number of Positions Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated	Manufacturer Part Number	SP06A-16-26S
Circular Connectors Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated MIL-DTL-26482 Series I, SP MIL - MIL-DTL-26482 Series I, SP Plug	Manufacturer	Amphenol Industrial Operations
Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated 600VAC		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL	Package	-
Number of Positions Shell Size - Insert 16-26 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated 26 Number of Positions 26 Free Hanging (In-Line) Normal Auminum (Ingress Protection 26 Aluminum (Ingress Protection 36) Gold Features - Voltage - Rated	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated 16-26 Aluminum, Anodic Coating (Alumilite) 600VAC	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated Onumber Hanging (In-Line) Aluminum Solder Cup Bayonet Lock N (Normal) Aluminum Solder Cup Aluminum Solder Cup Solder	Number of Positions	26
Mounting Type Free Hanging (In-Line) Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated Free Hanging (In-Line) Solder Cup Bayonet Lock N (Normal) - Gordat Footson Contact Finish Aluminum, Anodic Coating (Alumilite) Gold Features - Voltage - Rated	Shell Size - Insert	16-26
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated Orientation N (Normal) - 600VAC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Aluminum, Anodic Coating (Alumilite) Gold 600VAC	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC	Ingress Protection	-
Features - Voltage - Rated 600VAC	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 600VAC	Contact Finish	Gold
	Features	-
Current Rating 7.5A	Voltage - Rated	600VAC
7.012	Current Rating	7.5A
Report errors?		Report errors?

SP06A-16-26S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP06A-16-26S Payment Methods





















SP06A-16-26S Shipping Methods













If you have any question about SP06A-16-26S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com