

### SP06A-22-55S(SR) Information

Heisener.com

Part Number SP06A-22-55S(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors** 

CONN PLUG 55POS INLINE SKT **Description** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SP06A-22-55S(SR) Specifications

Manufacturer Part Number       SP06A-22-55S(SR)         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-26482 Series I, SP         Connector Type       Plug, Female Sockets         Number of Positions       55         Shell Size - Insert       22-55         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       -         Shell Material, Finish       Aluminum, Anodic Coating (Alumilite)         Contact Finish       Gold         Features       Strain Relief         Voltage - Rated       600VAC         Current Rating       7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-26482 Series I, SP  Connector Type Plug, Female Sockets  Number of Positions 55  Shell Size - Insert 22-55  Shell Size, MIL - Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Gold  Features Strain Relief  Voltage - Rated 600VAC  Current Rating 7.5A	Manufacturer Part Number	SP06A-22-55S(SR)
Circular Connectors  Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 7.5A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, SP  Connector Type Plug, Female Sockets  Number of Positions 55  Shell Size - Insert 22-55  Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Gold  Features Strain Relief  Voltage - Rated 600VAC  Current Rating 7.5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL		Circular Connectors
Connector Type Plug, Female Sockets  Number of Positions 55  Shell Size - Insert 22-55  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Gold  Features Strain Relief  Voltage - Rated 600VAC  Current Rating 7.5A	Package	-
Number of Positions  Shell Size - Insert  22-55  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  600VAC  Current Rating  7.5A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Features  Strain Relief  Voltage - Rated  Current Rating  7.5A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Gold  Features Strain Relief  Voltage - Rated Current Rating 7.5A	Number of Positions	55
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	22-55
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  600VAC  Current Rating  7.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Gold  Features Strain Relief  Voltage - Rated 600VAC  Current Rating 7.5A	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum, Anodic Coating (Alumilite)  Gold  Strain Relief  7.5A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	-
Features Strain Relief  Voltage - Rated 600VAC  Current Rating 7.5A	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Strain Relief
•	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

### SP06A-22-55S(SR) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SP06A-22-55S(SR) Payment Methods



















# SP06A-22-55S(SR) Shipping Methods













If you have any question about SP06A-22-55S(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com