

SP06CE-14-5P(304) Information

Heisener.com

For Reference Only

Part Number SP06CE-14-5P(304)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors**

Description CONN PLUG 5POS INLINE PIN

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP06CE-14-5P(304) Specifications

Manufacturer Part Number SP06CE-14-5P(304) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 1000VAC Current Rating 13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated1000VACCurrent Rating13A	Manufacturer Part Number	SP06CE-14-5P(304)
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated1000VACCurrent Rating13A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated1000VACCurrent Rating13A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated1000VACCurrent Rating13A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated1000VACCurrent Rating13A	Package	-
Number of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated1000VACCurrent Rating13A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated1000VACCurrent Rating13A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 1000VAC Current Rating	Number of Positions	5
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated1000VACCurrent Rating13A	Shell Size - Insert	14-5
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 1000VAC Current Rating 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 1000VAC Current Rating 13A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 1000VAC Current Rating 13A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 1000VAC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Features Voltage - Rated Current Rating 1000VAC 13A	Orientation	N (Normal)
Contact Finish - Features - Voltage - Rated 1000VAC Current Rating 13A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 1000VAC Current Rating 13A	Shell Material, Finish	-
Voltage - Rated 1000VAC Current Rating 13A	Contact Finish	-
Current Rating 13A	Features	-
	Voltage - Rated	1000VAC
Report errors?	Current Rating	13A
		Report errors?

SP06CE-14-5P(304) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP06CE-14-5P(304) Payment Methods



















SP06CE-14-5P(304) Shipping Methods













If you have any question about SP06CE-14-5P(304), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com