

SP06E-14-5P(SR) Information

Heisener.com

Part Number SP06E-14-5P(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 5POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP06E-14-5P(SR) Specifications

Manufacturer SP06E-14-5P(SR) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 13A	Manufacturer Part Number	SP06E-14-5P(SR)
Circular Connectors Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, SP Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, SP Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A		Circular Connectors
Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Package	-
Number of Positions Shell Size - Insert 14-5 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Strain Relief Voltage - Rated 1000VAC Current Rating	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Number of Positions	5
Mounting Type Free Hanging (In-Line) Termination Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating	Shell Size - Insert	14-5
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Termination	Solder Cup
Ingress Protection Environment Resistant Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 13A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 1000VAC Current Rating 13A	Contact Finish	Gold
Current Rating 13A	Features	Strain Relief
-	Voltage - Rated	1000VAC
Report errors?	Current Rating	13A
		Report errors?

SP06E-14-5P(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP06E-14-5P(SR) Payment Methods



















SP06E-14-5P(SR) Shipping Methods













If you have any question about SP06E-14-5P(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com