

SP06E-16-8S(SR) Information

Heisener.com

Part Number SP06E-16-8S(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 8POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP06E-16-8S(SR) Specifications

Manufacturer Part NumberSP06E-16-8S(SR)ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Female SocketsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Female SocketsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Manufacturer Part Number	SP06E-16-8S(SR)
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Female SocketsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 8 Shell Size - Insert 16-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 8 Shell Size - Insert 16-8 Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Package	-
Number of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Number of Positions	8
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Shell Size - Insert	16-8
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Termination	Solder Cup
Ingress Protection Environment Resistant Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating Aluminum, Anodic Coating (Alumilite) Gold Strain Relief 1000VAC	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 1000VAC Current Rating 13A	Contact Finish	Gold
Current Rating 13A	Features	Strain Relief
	Voltage - Rated	1000VAC
Report errors?	Current Rating	13A
		Report errors?

SP06E-16-8S(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP06E-16-8S(SR) Payment Methods



















SP06E-16-8S(SR) Shipping Methods













If you have any question about SP06E-16-8S(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com