

SP06E-22-55P(SR) Information

Heisener.com

Part Number SP06E-22-55P(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 55POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP06E-22-55P(SR) Specifications

Manufacturer Part NumberSP06E-22-55P(SR)ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Male PinsNumber of Positions55Shell Size - Insert22-55Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5AReport errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Male PinsNumber of Positions55Shell Size - Insert22-55Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	SP06E-22-55P(SR)
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Male PinsNumber of Positions55Shell Size - Insert22-55Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated600 VACCurrent Rating7.5A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, SP Connector Type Plug, Male Pins Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7, 5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, SP Connector Type Plug, Male Pins Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions55Shell Size - Insert22-55Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions55Shell Size - Insert22-55Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	55
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	22-55
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection Environment Resistant Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating Aluminum, Anodic Coating (Alumilite) Gold Strain Relief 7.5A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Strain Relief
-	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

SP06E-22-55P(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP06E-22-55P(SR) Payment Methods



















SP06E-22-55P(SR) Shipping Methods













If you have any question about SP06E-22-55P(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com