

SP06SE-14-12S Information

Heisener.com

Part Number SP06SE-14-12S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 12POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP06SE-14-12S Specifications

Manufacturer Part Number SP06SE-14-12S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated Connectors, Interconnects Circular Connectors HIL-DTL-26482 Series I, SP Plug, Female Sockets NIL-DTL-26482 Series I, SP Plug, Female Sockets NIL-DTL-26482 Series I, SP Plug, Female Sockets Number of Positions I 2 Shell Size - Insert I 4-12 Shell Size - Insert I 4-12 Shell Size - Insert I 4-12 Shell Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated	Manufacturer Part Number	SP06SE-14-12S
Circular Connectors Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated MIL-DTL-26482 Series I, SP MIL - MIL-DTL-26482 Series I, SP MIL-	Manufacturer	Amphenol Industrial Operations
Package - Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated 600VAC	Package	-
Number of Positions Shell Size - Insert 14-12 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated 12 14-12	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Voltage - Rated 14-12	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Voltage - Rated 600VAC	Number of Positions	12
Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC	Shell Size - Insert	14-12
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated Bayonet Lock N (Normal) Environment Resistant Aluminum, Anodic Coating (Alumilite) Gold Features -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 600VAC	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Aluminum, Anodic Coating (Alumilite) Gold 600VAC	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 600VAC	Contact Finish	Gold
	Features	-
Current Rating 7.5A, 13A	Voltage - Rated	600VAC
	Current Rating	7.5A, 13A
Report errors?		Report errors?

SP06SE-14-12S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP06SE-14-12S Payment Methods



















SP06SE-14-12S Shipping Methods













If you have any question about SP06SE-14-12S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com