



## SP06SE-20-16S(SR) Information

Heisener.com

Part Number SP06SE-20-16S(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors** 

**Description** CONN PLUG 16POS INLINE SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SP06SE-20-16S(SR) Specifications

Manufacturer       SP06SE-20-16S(SR)         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-26482 Series I, SP         Connector Type       Plug, Female Sockets         Number of Positions       16         Shell Size - Insert       20-16         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Anodic Coating (Alumilite)         Contact Finish       Gold         Features       Strain Relief         Voltage - Rated       1000VAC         Current Rating       13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Female SocketsNumber of Positions16Shell Size - Insert20-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Manufacturer Part Number	SP06SE-20-16S(SR)
Package-SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Female SocketsNumber of Positions16Shell Size - Insert20-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, SP Connector Type Plug, Female Sockets Number of Positions 16 Shell Size - Insert 20-16 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, SPConnector TypePlug, Female SocketsNumber of Positions16Shell Size - Insert20-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions16Shell Size - Insert20-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Package	-
Number of Positions16Shell Size - Insert20-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Features Strain Relief  Voltage - Rated 1000VAC  Current Rating 13A	Number of Positions	16
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Shell Size - Insert	20-16
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  1000VAC  Current Rating  13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 13A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Ingress Protection	Environment Resistant
Features Strain Relief  Voltage - Rated 1000VAC  Current Rating 13A	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 1000VAC Current Rating 13A	Contact Finish	Gold
Current Rating 13A	Features	Strain Relief
	Voltage - Rated	1000VAC
Report errors?	Current Rating	13A
		Report errors?

## SP06SE-20-16S(SR) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## SP06SE-20-16S(SR) Payment Methods



















## SP06SE-20-16S(SR) Shipping Methods













If you have any question about SP06SE-20-16S(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com