

SP1812-682J Information

Part Number SP1812-682J
Manufacturer API Delevan Inc.

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 6.8UH 878MA 260 MOHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP1812-682J Specifications

Manufacturer API Delevan Inc. Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series SP1812 Type - Material - Core Ferrite Inductance 6.8µH Tolerance ±5% Current Rating 878mA Current - Saturation 789mA Shielding Shielded DC Resistance (DCR) 260 mOhm Max Q @ Freq - Frequency - Self Resonant -	
Fixed Inductors	
Package Nonstandard Series SP1812 Type - Material - Core Ferrite Inductance 6.8μH Tolerance ±5% Current Rating 878mA Current - Saturation 789mA Shielding Shielded DC Resistance (DCR) 260 mOhm Max Q @ Freq -	
Series SP1812 Type - Material - Core Ferrite Inductance 6.8μH Tolerance ±5% Current Rating 878mA Current - Saturation 789mA Shielding Shielded DC Resistance (DCR) 260 mOhm Max Q @ Freq -	
Type - Material - Core Ferrite Inductance 6.8μH Tolerance ±5% Current Rating 878mA Current - Saturation 789mA Shielding Shielded DC Resistance (DCR) 260 mOhm Max Q @ Freq -	
Material - Core Ferrite Inductance 6.8μH Tolerance ±5% Current Rating 878mA Current - Saturation 789mA Shielding Shielded DC Resistance (DCR) 260 mOhm Max Q @ Freq -	
Inductance 6.8μH Tolerance ±5% Current Rating 878mA Current - Saturation 789mA Shielding Shielded DC Resistance (DCR) 260 mOhm Max Q @ Freq -	
Tolerance ±5% Current Rating 878mA Current - Saturation 789mA Shielding Shielded DC Resistance (DCR) 260 mOhm Max Q @ Freq -	
Current Rating 878mA Current - Saturation 789mA Shielding Shielded DC Resistance (DCR) 260 mOhm Max Q @ Freq -	
Current - Saturation 789mA Shielding Shielded DC Resistance (DCR) 260 mOhm Max Q @ Freq -	
Shielding Shielded DC Resistance (DCR) 260 mOhm Max Q @ Freq -	
DC Resistance (DCR) Q @ Freq -	
Q @ Freq -	
Frequency - Self Resonant -	
1 2	
Ratings -	
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Frequency - Test 1kHz	
Features -	
Mounting Type Surface Mount	
Package / Case Nonstandard	
Supplier Device Package -	
Size / Dimension 0.190" L x 0.134" W (4.83mm x 3.40mm)	

Height - Seated (Max)	0.134" (3.40mm)
	Report errors?

SP1812-682J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP1812-682J Payment Methods



















SP1812-682J Shipping Methods











If you have any question about SP1812-682J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com