



SP1812R-393K Information

Part Number SP1812R-393K Manufacturer API Delevan Inc.

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 39UH 354MA 1.6 OHM SMD

Package 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP1812R-393K Specifications

ManufacturerAPI Delevan Inc.CategoryInductors, Coils, ChokesFixed InductorsPackage1812 (4532 Metric)SeriesSP1812RType-Material - CoreFerriteInductance39μHTolerance±10%Current Rating354mACurrent - Saturation332mAShieldingShieldedDC Resistance (DCR)1.6 Ohm Max	
Fixed Inductors Package 1812 (4532 Metric) Series SP1812R Type - Material - Core Ferrite Inductance 39μH Tolerance ±10% Current Rating 354mA Current - Saturation 332mA Shielding Shielded	
Package 1812 (4532 Metric) Series SP1812R Type - Material - Core Ferrite Inductance 39μH Tolerance ±10% Current Rating 354mA Current - Saturation 332mA Shielding Shielded	
Series SP1812R Type - Material - Core Ferrite Inductance 39μH Tolerance ±10% Current Rating 354mA Current - Saturation 332mA Shielding Shielded	
Type - Material - Core Ferrite Inductance 39μH Tolerance ±10% Current Rating 354mA Current - Saturation 332mA Shielding Shielded	
$\begin{array}{ccc} \text{Material - Core} & \text{Ferrite} \\ \text{Inductance} & 39 \mu H \\ \text{Tolerance} & \pm 10 \% \\ \text{Current Rating} & 354 \text{mA} \\ \text{Current - Saturation} & 332 \text{mA} \\ \text{Shielding} & \text{Shielded} \\ \end{array}$	
$\begin{array}{ccc} Inductance & 39 \mu H \\ Tolerance & \pm 10 \% \\ Current Rating & 354 mA \\ Current - Saturation & 332 mA \\ Shielding & Shielded \\ \end{array}$	
Current Rating 354mA Current - Saturation 332mA Shielding Shielded	
Current - Saturation 332mA Shielding Shielded	
Shielding Shielded	
DC Resistance (DCR)	
De Resistance (Der.)	
Q @ Freq	
Frequency - Self Resonant -	
Ratings -	
Operating Temperature -55°C ~ 125°C	
Frequency - Test 1kHz	
Features -	
Mounting Type Surface Mount	
Package / Case 1812 (4532 Metric)	
Supplier Device Package 1812	
Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm	nm)

Height - Seated (Max)	0.134" (3.40mm)
	Report errors?

SP1812R-393K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP1812R-393K Payment Methods



















SP1812R-393K Shipping Methods













If you have any question about SP1812R-393K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com