



SP20C-G101 U Information

Heisener.com

Part Number SP20C-G101 U

Manufacturer Amphenol Advanced Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR GAUGE PRESSURE +/-.1 DIP

Package 6-DIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP20C-G101 U Specifications

Manufacturer Part NumberSP20C-G101 UManufacturerAmphenol Advanced SensorsCategorySensors, TransducersPackage6-DIP ModuleSeriesSPPressure TypeCompoundOperating Pressure±1.42 PSI (±9.79 kPa)Output TypeWheatstone BridgeOutput60 mV ~ 140 mVAccuracy-Voltage - Supply-Port SizeMale - 0.12" (3mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±4.27 PSI (±29.44 kPa)Operating Temperature-20°C ~ 100°CPackage / Case6-DIP ModuleSupplier Device Package-Report errors?		
CategorySensors, TransducersPackage6-DIP ModuleSeriesSPPressure TypeCompoundOperating Pressure±1.42 PSI (±9.79 kPa)Output TypeWheatstone BridgeOutput60 mV ~ 140 mVAccuracy-Voltage - Supply-Port SizeMale - 0.12" (3mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±4.27 PSI (±29.44 kPa)Operating Temperature-20°C ~ 100°CPackage / Case6-DIP ModuleSupplier Device Package-	Manufacturer Part Number	SP20C-G101 U
Package 6-DIP Module Series SP Pressure Type Compound Operating Pressure ±1.42 PSI (±9.79 kPa) Output Type Wheatstone Bridge Output 60 mV ~ 140 mV Accuracy - Voltage - Supply - Port Size Male - 0.12" (3mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±4.27 PSI (±29.44 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Manufacturer	Amphenol Advanced Sensors
Package 6-DIP Module Series SP Pressure Type Compound Operating Pressure ±1.42 PSI (±9.79 kPa) Output Type Wheatstone Bridge Output 60 mV ~ 140 mV Accuracy - Voltage - Supply - Port Size Male - 0.12" (3mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±4.27 PSI (±29.44 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Category	Sensors, Transducers
SeriesSPPressure TypeCompoundOperating Pressure±1.42 PSI (±9.79 kPa)Output TypeWheatstone BridgeOutput60 mV ~ 140 mVAccuracy-Voltage - Supply-Port SizeMale - 0.12" (3mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±4.27 PSI (±29.44 kPa)Operating Temperature-20°C ~ 100°CPackage / Case6-DIP ModuleSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Operating Pressure ±1.42 PSI (±9.79 kPa) Output Type Wheatstone Bridge Output 60 mV ~ 140 mV Accuracy - Voltage - Supply - Port Size Male - 0.12" (3mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±4.27 PSI (±29.44 kPa) Operating Temperature -20°C ~ 100°C Package / Case Supplier Device Package -	Package	6-DIP Module
Operating Pressure ±1.42 PSI (±9.79 kPa) Output Type Wheatstone Bridge Output 60 mV ~ 140 mV Accuracy - Voltage - Supply - Port Size Male - 0.12" (3mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±4.27 PSI (±29.44 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package	Series	SP
Output TypeWheatstone BridgeOutput60 mV ~ 140 mVAccuracy-Voltage - Supply-Port SizeMale - 0.12" (3mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±4.27 PSI (±29.44 kPa)Operating Temperature-20°C ~ 100°CPackage / Case6-DIP ModuleSupplier Device Package-	Pressure Type	Compound
Output 60 mV ~ 140 mV Accuracy - Voltage - Supply - Port Size Male - 0.12" (3mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±4.27 PSI (±29.44 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Operating Pressure	±1.42 PSI (±9.79 kPa)
Accuracy Voltage - Supply Port Size Male - 0.12" (3mm) Tube Barbless Features - Termination Style Maximum Pressure Deprating Temperature Package / Case G-DIP Module Supplier Device Package - Came And Accuracy - Male - 0.12" (3mm) Tube Barbless PC Pin +4.27 PSI (±29.44 kPa) -20°C ~ 100°C 6-DIP Module	Output Type	Wheatstone Bridge
Voltage - Supply-Port SizeMale - 0.12" (3mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±4.27 PSI (±29.44 kPa)Operating Temperature-20°C ~ 100°CPackage / Case6-DIP ModuleSupplier Device Package-	Output	60 mV ~ 140 mV
Port Size Male - 0.12" (3mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±4.27 PSI (±29.44 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Accuracy	-
Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±4.27 PSI (±29.44 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package	Voltage - Supply	-
Features - Termination Style PC Pin Maximum Pressure ±4.27 PSI (±29.44 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Port Size	Male - 0.12" (3mm) Tube
Termination Style PC Pin Maximum Pressure ±4.27 PSI (±29.44 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Port Style	Barbless
Maximum Pressure ±4.27 PSI (±29.44 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Features	-
Operating Temperature-20°C ~ 100°CPackage / Case6-DIP ModuleSupplier Device Package-	Termination Style	PC Pin
Package / Case 6-DIP Module Supplier Device Package -	Maximum Pressure	±4.27 PSI (±29.44 kPa)
Supplier Device Package -	Operating Temperature	-20°C ~ 100°C
	Package / Case	6-DIP Module
Report errors?	Supplier Device Package	-
		Report errors?

SP20C-G101 U Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP20C-G101 U Payment Methods





















SP20C-G101 U Shipping Methods













If you have any question about SP20C-G101 U, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com