

SP211EHEA-L/TR

SP211EHEA-L/TR Information

unnunnin www.commer.com RRRRRR	 SP211EHEA-L/TR Exar Corporation Integrated Circuits (ICs) Interface - Drivers, Receivers, Transceivers IC TXRX RS232 MULTI-CH 28SSOP 28-SSOP (0.209", 5.30mm Width) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SP211EHEA-L/TR Specifications

ManufacturerExar CorporationCategoryIntegrated Circuits (ICs)Interface - Drivers, Receivers, TransceiversPackage28-SSOP (0.209", 5.30mm Width)Package-TypeTransceiverProtocolRS232Number of Drivers/Receivers4/5Ouplex500mVPactage230kbpsOutage - Supply4.5 V ~ 5.5 VOperating Temperature40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOPSupplier Device Package28-SSOP		
CategoryIntegrated Circuits (ICs)Interface - Drivers, Receivers, TransceiversPackage28-SSOP (0.209", 5.30mm Width)Series-FypeTransceiverProtocolRS232Number of Drivers/Receivers4/5DuplexFullReceiver Hysteresis500mVData Rate230kbpsVoltage - Supply4.5 V ~ 5.5 VDeperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Manufacturer Part Number	SP211EHEA-L/TR
Interface - Drivers, Receivers, TransceiversPackage28-SSOP (0.209", 5.30mm Width)Series-TypeTransceiverPypeTransceiverProtocolRS232Number of Drivers/Receivers4/5DuplexFullReceiver Hysteresis500mVData Rate230kbpsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Manufacturer	Exar Corporation
Package 28-SSOP (0.209", 5.30mm Width) Series - Type Transceiver Protocol RS232 Number of Drivers/Receivers 4/5 Duplex Full Receiver Hysteresis 500mV Data Rate 230kbps Operating Temperature 4.5 V ~ 5.5 V Operating Temperature Surface Mounting Type Package / Case 28-SSOP (0.209", 5.30mm Width)	Category	Integrated Circuits (ICs)
Series-FypeTransceiverProtocolRS232Number of Drivers/Receivers4/5DuplexFullReceiver Hysteresis500mVData Rate230kbpsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP		Interface - Drivers, Receivers, Transceivers
FypeTransceiverProtocolRS232Number of Drivers/Receivers4/5DuplexFullReceiver Hysteresis500mVData Rate230kbpsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)	Package	28-SSOP (0.209", 5.30mm Width)
ProtocolRS232Number of Drivers/Receivers4/5DuplexFullReceiver Hysteresis500mVData Rate230kbpsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Series	-
Number of Drivers/Receivers4/5OuplexFullReceiver Hysteresis500mVOata Rate230kbpsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Туре	Transceiver
DuplexFullReceiver Hysteresis500mVData Rate230kbpsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Protocol	RS232
Receiver Hysteresis500mVData Rate230kbpsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Number of Drivers/Receivers	4/5
Data Rate230kbpsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Duplex	Full
Voltage - Supply4.5 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Receiver Hysteresis	500mV
Deperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Data Rate	230kbps
Mounting TypeSurface MountPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Voltage - Supply	4.5 V ~ 5.5 V
Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Supplier Device Package 28-SSOP	Mounting Type	Surface Mount
	Package / Case	28-SSOP (0.209", 5.30mm Width)
Report errors?	Supplier Device Package	28-SSOP
		Report errors?

SP211EHEA-L/TR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

SP211EHEA-L/TR Payment Methods



SP211EHEA-L/TR Shipping Methods



If you have any question about SP211EHEA-L/TR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com