

SP4-DC36V Information

Heisener.com

Part Number SP4-DC36V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 10A 36V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SP4-DC36V Specifications

Manufacturer Part NumberSP4-DC36VManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesSPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage36VDCContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)25.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)		
CategoryRelaysPackage-SeriesSPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage36VDCContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)25.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Manufacturer Part Number	SP4-DC36V
Package-SeriesSPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage36VDCContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)25.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Manufacturer	Panasonic Electric Works
Package - Series SP Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 36VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 25.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Category	Relays
SeriesSPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage36VDCContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)25.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 36VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 25.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Package	-
Coil TypeNon LatchingCoil Current8.3mACoil Voltage36VDCContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)25.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Series	SP
Coil Current 8.3mA Coil Voltage 36VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 25.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Relay Type	General Purpose
Coil Voltage 36VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 25.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 25.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Current	8.3mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 25.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 20ms Features - Mounting Type Socketable Termination Style 10A 250VAC, 30VDC - Max 25.2 VDC 3.6 VDC 3.6 VDC 30ms Features - Plug In, Quick Connect - 0.187" (4.7mm)	Coil Voltage	36VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 25.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 30ms Release Time 20ms Features - Mounting Type Socketable Termination Style 25.2 VDC 3.6 VDC 3.6 VDC 30ms 40ms Forestarres - Mounting Type Socketable Plug In, Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 30ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Switching Voltage	250VAC, 30VDC - Max
Operate Time 30ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	25.2 VDC
Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	3.6 VDC
Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Operate Time	30ms
Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Release Time	20ms
Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Features	-
	Mounting Type	Socketable
Papart arrors?	Termination Style	Plug In, Quick Connect - 0.187" (4.7mm)
Report errors?		Report errors?

SP4-DC36V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SP4-DC36V Payment Methods



















SP4-DC36V Shipping Methods













If you have any question about SP4-DC36V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com