



## **SPFI002.T Information**

A Heisener.com

Part NumberSPFI002.TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 2A 1KVDC CYLINDR

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **SPFI002.T Specifications**

Manufacturer Part NumberSPF1002.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Manufacturer Part Number	SPFI002.T
PackageElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Category	Circuit Protection
SeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating2AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Package	Cylindrical, Blade Terminals
Current Rating  Voltage Rating - AC  Voltage Rating - DC  1000V (1kV)  Response Time  Fast  Applications  Solar (Photovoltaic)  Features  - Class  - Approvals  CE, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  2A  1000V (1kV)  Fast  CE, UR  Columber CE, UR  CE, UR  Columber Columb	Series	POWR-GARD? SPFI
Voltage Rating - AC  Voltage Rating - DC  1000V (1kV)  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  - Closs - Class CE, UR CE, UR COPERATE CAPACITY (Pasted Voltage) COPERATE	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  1000V (1kV) Fast  Fast CDOUT (10.31mm x 63.50mm)	Current Rating	2A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Fast Solar (Photovoltaic) Fast CR Foliat (Photovoltaic) Fast CR Fast Solar (Photovoltaic) Fast CR Fast Solar (Photovoltaic) Features CR Solar (Photovoltaic) Features Features Solar (Photovoltaic) Features F	Voltage Rating - AC	-
Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Solar (Photovoltaic) - CE, UR CE, UR CE, UR COLUMB CARROW CE, UR COLUMB CARROW COLUMB CARROW COLUMB CARROW CE, UR COLUMB CARROW	Voltage Rating - DC	1000V (1kV)
Features - Class - CE, UR  Approvals CE, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 20kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Response Time	Fast
Class - CE, UR  Operating Temperature - Streaking Capacity @ Rated Voltage 20kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Applications	Solar (Photovoltaic)
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension  CE, UR  - Culture - Culture - Cylindrical, Blade Terminals 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Class	-
Breaking Capacity @ Rated Voltage 20kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Approvals	CE, UR
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Breaking Capacity @ Rated Voltage	20kA
Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	0.406" Dia x 2.500" L (10.31mm x 63.50mm)
		Report errors?

#### **SPFI002.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **SPFI002.T Payment Methods**





















## **SPFI002.T Shipping Methods**













If you have any question about SPFI002.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com