



SPFI006.L Information

Manufa Categor Heisener.com

Part NumberSPFI006.LManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 6A 1KVDC CYLINDR

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SPFI006.L Specifications

Manufacturer Part NumberSPF1006.LManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Manufacturer Part Number	SPFI006.L
PackageElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Category	Circuit Protection
SeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating6AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Package	Cylindrical, Blade Terminals
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals Cperating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 6A A 6A 6A 6A 6A 6A 6A 6A 6B 6B	Series	POWR-GARD? SPFI
Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - 1000V (1kV) Fast Fast Fast - 1000V (1kV) Fast Fast Fast - 1000V (1kV) Fast	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 1000V (1kV) Fast Fast CDOUT (10.31mm x 63.50mm) Fast CE, UR CE, UR CE, UR COLUMN CE, UR CE,	Current Rating	6A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Fast Solar (Photovoltaic) Fast Fast Chylotovoltaic) Feature - CE, UR - CE, UR - COPRAGE CUR - CU	Voltage Rating - AC	-
Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Voltage Rating - DC	1000V (1kV)
Features - Class - CE, UR Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Response Time	Fast
Class - CE, UR Operating Temperature - Streaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Applications	Solar (Photovoltaic)
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension CE, UR - Culture - Culture - Cylindrical, Blade Terminals 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Class	-
Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Approvals	CE, UR
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Breaking Capacity @ Rated Voltage	20kA
Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	0.406" Dia x 2.500" L (10.31mm x 63.50mm)
_		Report errors?

SPFI006.L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SPFI006.L Payment Methods





















SPFI006.L Shipping Methods













If you have any question about SPFI006.L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com