



### **SPFI015.T Information**

Manufacturer Littelfuse Inc. Category Heisener.com

Circuit Protection Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 15A 1KVDC CYLINDR

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

Part Number SPFI015.T

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **SPFI015.T Specifications**

Manufacturer Part NumberSPFI015.TManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Manufacturer Part Number	SPFI015.T
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminals Series POWR-GARD? SPFI Fuse Type Cartridge Current Rating 15A Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals Cyerting Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension  Electrical, Specialty Fuses Cylindrical, Blade Terminals Size / Dimension  Electrical, Specialty Fuses Cylindrical, Blade Terminals Size / Dimension  Electrical, Specialty Fuses Specialty Fu	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Category	Circuit Protection
SeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 15A Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge 1000V (1kV) CHOUSE ADDRESS ACCOUNTS	Package	Cylindrical, Blade Terminals
Current Rating Voltage Rating - AC  Voltage Rating - DC  Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  15A  15A  16A  16D  16D  16D  16D  16D  16D  16	Series	POWR-GARD? SPFI
Voltage Rating - AC  Voltage Rating - DC  1000V (1kV)  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  -  1000V (1kV)  -  1000V (1k	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  1000V (1kV) Fast  Fast CR  Fast  Collabor  Foat  Past  Foat  Past  CE, UR  CE, UR  COJENT  CE, UR  COJENT  CE, UR  COJENT  COJ	Current Rating	15A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Fast Solar (Photovoltaic) Fast Characteristics - CE, UR - CE, UR - CE, UR - CE, UR - CUR -	Voltage Rating - AC	-
Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Solar (Photovoltaic) - CE, UR CE, UR CE, UR COLUMB	Voltage Rating - DC	1000V (1kV)
Features - Class - CE, UR  Approvals CE, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 20kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Response Time	Fast
Class - CE, UR  Operating Temperature - Streaking Capacity @ Rated Voltage 20kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Applications	Solar (Photovoltaic)
Approvals  CE, UR  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  O.406" Dia x 2.500" L (10.31mm x 63.50mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Class	-
Breaking Capacity @ Rated Voltage 20kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Approvals	CE, UR
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Breaking Capacity @ Rated Voltage	20kA
Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	0.406" Dia x 2.500" L (10.31mm x 63.50mm)
		Report errors?

#### **SPFI015.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **SPFI015.T Payment Methods**





















### **SPFI015.T Shipping Methods**













If you have any question about SPFI015.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com