



### **SPFI030.T Information**

Heisener.com

For Reference Only

Part NumberSPFI030.TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 30A 1KVDC CYLINDR

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **SPFI030.T Specifications**

Manufacturer Part Number         SPFI030.T           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Electrical, Specialty Fuses           Package         Cylindrical, Blade Terminals           Series         POWR-GARD? SPFI           Fuse Type         Cartridge           Current Rating         30A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         Holder           Package / Case         Cylindrical, Blade Terminals           Size / Dimension         0.406" Dia x 2.500" L (10.31mm x 63.50mm)    Report errors?		
Category  Circuit Protection Electrical, Specialty Fuses  Package Cylindrical, Blade Terminals  Series POWR-GARD? SPFI  Fuse Type Cartridge Current Rating 30A  Voltage Rating - AC Voltage Rating - DC 1000V (1kV)  Response Time Fast Applications Solar (Photovoltaic)  Features - Class - Approvals CE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension  Circuit Protection Electrical, Specialty Fuses  Lectrical, Specialty Fuses  Circuit Protection Electrical, Specialty Fuses  Electrical, Specialty Fuses  Logindrical, Blade Terminals  Size / Dimension  Circuit Protection Electrical, Specialty Fuses  Lectrical, Specialty Lectricals  Lectrical, Specialty Fuses  Lectrical Specialty Fuses  Lectrical Specialty Fuses  Lectrical Specialty Fuses  Lectrical Special Speci	Manufacturer Part Number	SPFI030.T
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminals Series POWR-GARD? SPFI Fuse Type Cartridge Current Rating 30A Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals Cyerting Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension  Electrical, Specialty Fuses Cylindrical, Blade Terminals Size / Dimension  Electrical, Specialty Fuses Cylindrical, Blade Terminals Size / Dimension  Electrical, Specialty Fuses Specialty Fu	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Category	Circuit Protection
SeriesPOWR-GARD? SPFIFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating30AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Package	Cylindrical, Blade Terminals
Current Rating Voltage Rating - AC  Voltage Rating - DC  Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  30A	Series	POWR-GARD? SPFI
Voltage Rating - AC  Voltage Rating - DC  1000V (1kV)  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  -  1000V (1kV)  -  1000V (1k	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  1000V (1kV) Fast  Fast CR  Fast  CUR  - CE, UR  CE, UR  CUR  CUR  CUR  CUR  CUR  COPIT HOLDER  COVING TEMPERATUR  COVING TEMPERATUR	Current Rating	30A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Fast Solar (Photovoltaic) Fast Characteristics Solar (Photovoltaic) - CE, UR CE, UR - CE, UR - CUR - CU	Voltage Rating - AC	-
Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Solar (Photovoltaic) - CE, UR CE, UR CE, UR COLUMB	Voltage Rating - DC	1000V (1kV)
Features - Class - CE, UR  Approvals CE, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 20kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Response Time	Fast
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Applications	Solar (Photovoltaic)
Approvals  CE, UR  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  O.406" Dia x 2.500" L (10.31mm x 63.50mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Class	-
Breaking Capacity @ Rated Voltage 20kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Approvals	CE, UR
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Breaking Capacity @ Rated Voltage	20kA
Size / Dimension 0.406" Dia x 2.500" L (10.31mm x 63.50mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	0.406" Dia x 2.500" L (10.31mm x 63.50mm)
		Report errors?

#### **SPFI030.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **SPFI030.T Payment Methods**





















### **SPFI030.T Shipping Methods**













If you have any question about SPFI030.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com