



SPN150-15S Information



For Reference Only

Part Number SPN150-15S

Manufacturer Volgen America/Kaga Electronics USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 15V 150W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SPN150-15S Specifications

Manufacturer Part Number SPN150-15S Manufacturer Volgen America/Kaga Electronics USA Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SPN150 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm) Report errors?	_		
Category Power Supplies - External/Internal (Off-Board) Ac DC Converters Package - Series SPN150 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Manufacturer Part Number	SPN150-15S	
Package - Series SPN150 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Manufacturer	Volgen America/Kaga Electronics USA	
Package - Series SPN150 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series SPN150 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)		AC DC Converters	
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Package	-	
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Series	SPN150	
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Туре	Enclosed	
Voltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10APower (Watts)150WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency87%Operating Temperature0°C ~ 60°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Voltage - Input	85 ~ 264 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Voltage - Output 1	15V	
Voltage - Output 4 Current - Output (Max) 10A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Voltage - Output 2	-	
Current - Output (Max) 10A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Voltage - Output 4	-	
ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency 87% Operating Temperature $0^{\circ}C \sim 60^{\circ}C$ (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension 7.72 " L x 4.21 " W x 1.77 " H (196.0mm x 107.0 mm x 45.0 mm)	Current - Output (Max)	10A	
Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Power (Watts)	150W	
Efficiency 87% Operating Temperature 0°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Applications	ITE (Commercial)	
Operating Temperature 0°C ~ 60°C (With Derating) Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Voltage - Isolation	3kV (3000V)	
Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Efficiency	87%	
Mounting Type Chassis Mount Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)	
Size / Dimension 7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	Features	Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	7.72" L x 4.21" W x 1.77" H (196.0mm x 107.0mm x 45.0mm)	
			Report errors?

SPN150-15S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SPN150-15S Payment Methods



















SPN150-15S Shipping Methods













If you have any question about SPN150-15S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com