

SPTMA0015PG5W02

SPTMA0015PG5W02 Information



For Reference Only

Part Number SPTMA0015PG5W02

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 15PSIG STEEL 4-20MA OUT

Package Cylinder

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SPTMA0015PG5W02 Specifications

Manufacturer Part Number SPTMA0015PG5W02 Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder Series SPT Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 12.5 V ~ 24 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -40°C ~ 85°C Supplier Davice Package / Case Cylinder		
CategorySensors, TransducersPackageCylinderSeriesSPTPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply12.5 V ~ 24 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleCable 2'Maximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseCylinder	Manufacturer Part Number	SPTMA0015PG5W02
Pressure Sensors, Transducers Cylinder Series SPT Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 12.5 V ~ 24 V Port Size Male - 1/4" (6.35mm) NPT Port Style Features Temperature Compensated Termination Style Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinderSeriesSPTPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply12.5 V ~ 24 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleCable 2'Maximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseCylinder	Category	Sensors, Transducers
Series SPT Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 12.5 V ~ 24 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder		Pressure Sensors, Transducers
Pressure Type Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 12.5 V ~ 24 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case Vented Gauge Wheatstone 15 PSI (103.42 kPa) Vheatstone Heatstone 15 PSI (103.42 kPa) Vheatstone 16 PSI (200.42 kPa) Vheatstone 17 PSI (200.42 kPa) Vheatstone 18 PSI (310.26 kPa) Vented Gauge 19 PSI (310.26 kPa) Vheatstone 19 PSI (310.26 kPa) Vhe	Package	Cylinder
Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 12.5 V ~ 24 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder	Series	SPT
Output Type Wheatstone Bridge Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 12.5 V ~ 24 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder	Pressure Type	Vented Gauge
Output $4 \text{ mA} \sim 20 \text{ mA}$ Accuracy $\pm 0.25\%$ Voltage - Supply $12.5 \text{ V} \sim 24 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleCable 2'Maximum Pressure $45 \text{ PSI (310.26 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseCylinder	Operating Pressure	15 PSI (103.42 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $12.5 \text{ V} \sim 24 \text{ V}$ Port Size $Male - 1/4$ " $(6.35\text{mm}) \text{ NPT}$ Port Style $Threaded$ Features $Temperature Compensated$ Termination Style $Cable 2$ ' Maximum Pressure $Cable 2$ ' Maximum Pressure $Cable 2$ ' Maximum Pressure $Cable 2$ ' Operating Temperature $Cable 2$ ' Package / Case $Cylinder$	Output Type	Wheatstone Bridge
Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder	Output	4 mA ~ 20 mA
Port Size Male - $1/4$ " (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -40°C ~ 85 °C Package / Case Cylinder	Accuracy	±0.25%
Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder	Voltage - Supply	12.5 V ~ 24 V
FeaturesTemperature CompensatedTermination StyleCable 2'Maximum Pressure $45 \text{ PSI } (310.26 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseCylinder	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style Cable 2' Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Cylinder	Port Style	Threaded
Maximum Pressure $45 \text{ PSI } (310.26 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseCylinder	Features	Temperature Compensated
Operating Temperature -40°C ~ 85°C Package / Case Cylinder	Termination Style	Cable 2'
Package / Case Cylinder	Maximum Pressure	45 PSI (310.26 kPa)
	Operating Temperature	-40°C ~ 85°C
Supplier Davica Packaga	Package / Case	Cylinder
Supplied Device I dekage	Supplier Device Package	-
Report errors?		Report errors?

SPTMA0015PG5W02 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SPTMA0015PG5W02 Payment Methods



















SPTMA0015PG5W02 Shipping Methods













If you have any question about SPTMA0015PG5W02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com