

SPTMA0500PG5W02

SPTMA0500PG5W02 Information



For Reference Only

Part Number SPTMA0500PG5W02

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 500PSIG STEEL 4-20MA OUT

Package Cylinde

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SPTMA0500PG5W02 Specifications

Manufacturer Part NumberSPTMA0500PG5W02ManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackageCylinderSeriesSPTPressure TypeVented GaugeOperating Pressure500 PSI (3447.38 kPa)Output TypeWheatstone BridgeOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply12.5 V ~ 24 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleCable 2'Maximum Pressure1200 PSI (8273.71 kPa)Operating Temperature-40°C ~ 85°C		
Category Sensors, Transducers Package Cylinder Series SPT Pressure Type Vented Gauge Operating Pressure 500 PSI (3447.38 kPa) Output Type Wheatstone Bridge Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Features Temperature Compensated Termination Style Maximum Pressure Sensors, Transducers Pressure Sensors, Transducers Acylinder Sensors, Transducers SPT Vented Gauge Wheatstone Bridge Vented Gauge Ven	Manufacturer Part Number	SPTMA0500PG5W02
Package Cylinder Series SPT Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 12.5 V ~ 24 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 1200 PSI (8273.71 kPa)	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinderSeriesSPTPressure TypeVented GaugeOperating Pressure500 PSI (3447.38 kPa)Output TypeWheatstone BridgeOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply12.5 V ~ 24 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleCable 2'Maximum Pressure1200 PSI (8273.71 kPa)	Category	Sensors, Transducers
Series SPT Pressure Type Vented Gauge Operating Pressure 500 PSI (3447.38 kPa) Output Type Wheatstone Bridge Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 12.5 V ~ 24 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 1200 PSI (8273.71 kPa)		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 500 PSI (3447.38 kPa) Output Type Wheatstone Bridge Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 12.5 V ~ 24 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 1200 PSI (8273.71 kPa)	Package	Cylinder
Operating Pressure 500 PSI (3447.38 kPa) Output Type Wheatstone Bridge Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 12.5 V ~ 24 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Maximum Pressure 1200 PSI (8273.71 kPa)	Series	SPT
Output TypeWheatstone BridgeOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply12.5 V ~ 24 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleCable 2'Maximum Pressure1200 PSI (8273.71 kPa)	Pressure Type	Vented Gauge
Output $4 \text{ mA} \sim 20 \text{ mA}$ Accuracy $\pm 0.25\%$ Voltage - Supply $12.5 \text{ V} \sim 24 \text{ V}$ Port Size $Male - 1/4" (6.35 \text{mm}) \text{ NPT}$ Port Style $Threaded$ Features $Temperature Compensated$ Termination Style $Cable 2'$ Maximum Pressure $Cable 2'$	Operating Pressure	500 PSI (3447.38 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $12.5 \text{ V} \sim 24 \text{ V}$ Port Size $\text{Male} - 1/4'' (6.35 \text{mm}) \text{ NPT}$ Port Style Threaded Features $\text{Temperature Compensated}$ Termination Style Cable 2' Maximum Pressure $1200 \text{ PSI (8273.71 kPa)}$	Output Type	Wheatstone Bridge
Voltage - Supply $12.5 \text{ V} \sim 24 \text{ V}$ Port Size $\text{Male - 1/4" (6.35 mm) NPT}$ Port Style Threaded Features $\text{Temperature Compensated}$ Termination Style Cable 2' Maximum Pressure $1200 \text{ PSI (8273.71 kPa)}$	Output	4 mA ~ 20 mA
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 1200 PSI (8273.71 kPa)	Accuracy	±0.25%
Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 1200 PSI (8273.71 kPa)	Voltage - Supply	12.5 V ~ 24 V
Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 1200 PSI (8273.71 kPa)	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style Cable 2' Maximum Pressure 1200 PSI (8273.71 kPa)	Port Style	Threaded
Maximum Pressure 1200 PSI (8273.71 kPa)	Features	Temperature Compensated
	Termination Style	Cable 2'
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Maximum Pressure	1200 PSI (8273.71 kPa)
	Operating Temperature	-40°C ~ 85°C
Package / Case Cylinder	Package / Case	Cylinder
Supplier Device Package -	Supplier Device Package	-
Report errors?		Report errors?

SPTMA0500PG5W02 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SPTMA0500PG5W02 Payment Methods



















SPTMA0500PG5W02 Shipping Methods













If you have any question about SPTMA0500PG5W02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com