

SPTMV0300PG5W02

SPTMV0300PG5W02 Information



For Reference Only

Part Number SPTMV0300PG5W02

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 300PSIG STEEL 100MV OUT

Package Cylinde

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SPTMV0300PG5W02 Specifications

Manufacturer Part Number SPTMV0300PG5W02 Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder Series SPT Pressure Type Vented Gauge Operating Pressure 300 PSI (2068.43 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.25% Voltage - Supply 10 V ~ 15 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder Supplier Device Package -		
CategorySensors, TransducersPackageCylinderSeriesSPTPressure TypeVented GaugeOperating Pressure300 PSI (2068.43 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.25%Voltage - Supply10 V ~ 15 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleCable 2'Maximum Pressure900 PSI (6205.28 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	SPTMV0300PG5W02
Package Cylinder Series SPT Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output (10 m) V ~ 100 mV (10V) Accuracy ±0.25% Voltage - Supply 10 V ~ 15 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature - 40°C ~ 85°C Package / Case Supplier Device Package Pressure SPT Cylinder Supplier Device Package Cylinder Cylinder Cylinder Cylinder Cylinder Supplier Device Package Cylinder	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinderSeriesSPTPressure TypeVented GaugeOperating Pressure300 PSI (2068.43 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.25%Voltage - Supply10 V ~ 15 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleCable 2'Maximum Pressure900 PSI (6205.28 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesSPTPressure TypeVented GaugeOperating Pressure300 PSI (2068.43 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.25%Voltage - Supply10 V ~ 15 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleCable 2'Maximum Pressure900 PSI (6205.28 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure300 PSI (2068.43 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.25%Voltage - Supply10 V ~ 15 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleCable 2'Maximum Pressure900 PSI (6205.28 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseCylinderSupplier Device Package-	Package	Cylinder
Operating Pressure Output Type Wheatstone Bridge Output Output OmV ~ 100 mV (10V) Accuracy ±0.25% Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 85°C Package / Case Supplier Device Package - Supplier Device Package	Series	SPT
Output Type Output OmV ~ 100 mV (10V) Accuracy ±0.25% Voltage - Supply In V ~ 15 V Port Size Male - 1/4" (6.35mm) NPT Port Style Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 85°C Package / Case Supplier Device Package -	Pressure Type	Vented Gauge
Output 0 mV ~ 100 mV (10V) Accuracy ±0.25% Voltage - Supply 10 V ~ 15 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder Supplier Device Package -	Operating Pressure	300 PSI (2068.43 kPa)
Accuracy ±0.25% Voltage - Supply 10 V ~ 15 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder Supplier Device Package -	Output Type	Wheatstone Bridge
Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder Supplier Device Package -	Output	$0 \text{ mV} \sim 100 \text{ mV} (10 \text{V})$
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder Supplier Device Package -	Accuracy	$\pm 0.25\%$
Port Style Threaded Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	10 V ~ 15 V
Features Temperature Compensated Termination Style Cable 2' Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style Cable 2' Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 85°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure900 PSI (6205.28 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseCylinderSupplier Device Package-	Features	Temperature Compensated
Operating Temperature -40°C ~ 85°C Package / Case Cylinder Supplier Device Package -	Termination Style	Cable 2'
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	900 PSI (6205.28 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
report errors.		Report errors?

SPTMV0300PG5W02 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SPTMV0300PG5W02 Payment Methods



















SPTMV0300PG5W02 Shipping Methods













If you have any question about SPTMV0300PG5W02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com