



SPXI012.L Information

Heisener.com

Part Number SPXI012.L

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 12A 1.5KVDC INLINE

Package Cartridge, Inline, Double Ended

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SPXI012.L Specifications

| Manufacturer Part Number SPXI012.L Manufacturer Littelfuse Inc. Category Circuit Protection Package Cartridge, Inline, Double Ended Series POWR-GARD? SPXI Fuse Type Cartridge Current Rating 12A Voltage Rating - AC - Voltage Rating - DC 1500V (1.5kV) Response Time - Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | | |
|--|-----------------------------------|---|
| Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Inline, Double Ended Series POWR-GARD? SPXI Fuse Type Cartridge Current Rating 12A Voltage Rating - AC Voltage Rating - DC 1500V (1.5kV) Response Time - Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension Circuit Protection Electrical, Specialty Fuses POWR-GARD? SPXI Factory In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Special Fuses Electrical, Special Fuses Electrical, Special Fuses Electrical, Power Fuses | Manufacturer Part Number | SPXI012.L |
| Beckage Cartridge, Inline, Double Ended Series POWR-GARD? SPXI Fuse Type Cartridge Current Rating 12A Voltage Rating - AC - Voltage Rating - DC 1500V (1.5kV) Response Time - Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 16MR SPXIII 15MR SPXI | Manufacturer | Littelfuse Inc. |
| PackageCartridge, Inline, Double EndedSeriesPOWR-GARD? SPXIFuse TypeCartridgeCurrent Rating12AVoltage Rating - AC-Voltage Rating - DC1500V (1.5kV)Response Time-ApplicationsSolar (Photovoltaic)FeaturesIntrinsically SafeClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage15kAMounting TypeIn LinePackage / CaseCartridge, Inline, Double EndedSize / Dimension0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Category | Circuit Protection |
| SeriesPOWR-GARD? SPXIFuse TypeCartridgeCurrent Rating12AVoltage Rating - AC-Voltage Rating - DC1500V (1.5kV)Response Time-ApplicationsSolar (Photovoltaic)FeaturesIntrinsically SafeClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage15kAMounting TypeIn LinePackage / CaseCartridge, Inline, Double EndedSize / Dimension0.406" Dia x 3.475" L (10.31mm x 88.27mm) | | Electrical, Specialty Fuses |
| Fuse Type Current Rating 12A Voltage Rating - AC - Voltage Rating - DC 1500V (1.5kV) Response Time - Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Package | Cartridge, Inline, Double Ended |
| Current Rating Voltage Rating - AC Voltage Rating - DC 1500V (1.5kV) Response Time - Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type In Line Package / Case Size / Dimension 12A - 1500V (1.5kV) - Solar (Photovoltaic) - Solar (Photovoltaic) - Solar (Photovoltaic) - Litrinsically Safe - Catridge, Inline, Double Ended 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Series | POWR-GARD? SPXI |
| Voltage Rating - AC Voltage Rating - DC 1500V (1.5kV) Response Time Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type In Line Package / Case Size / Dimension - 1500V (1.5kV) - 1500V | Fuse Type | Cartridge |
| Voltage Rating - DC Response Time - Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type In Line Package / Case Size / Dimension 1500V (1.5kV) 1500V (1.5kV) 1500V (1.5kV) 1500V (1.5kV) 16100V | Current Rating | 12A |
| Response Time Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension - Color (Photovoltaic) Intrinsically Safe - Intrinsically Safe - Class - Cartridge, Inline, Double Ended 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Voltage Rating - AC | - |
| Applications Features Intrinsically Safe Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension Solar (Photovoltaic) Intrinsically Safe - Cartridge, Inline, Double Ended 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Voltage Rating - DC | 1500V (1.5kV) |
| Features Intrinsically Safe Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Response Time | - |
| Class - Approvals - Coperating Temperature - Streaking Capacity @ Rated Voltage 15kA In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Applications | Solar (Photovoltaic) |
| Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Features | Intrinsically Safe |
| Operating Temperature Breaking Capacity @ Rated Voltage 15kA Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Class | - |
| Breaking Capacity @ Rated Voltage 15kA Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Approvals | - |
| Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Operating Temperature | - |
| Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Breaking Capacity @ Rated Voltage | 15kA |
| Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm) | Mounting Type | In Line |
| | Package / Case | Cartridge, Inline, Double Ended |
| Report errors? | Size / Dimension | 0.406" Dia x 3.475" L (10.31mm x 88.27mm) |
| | | Report errors? |

SPXI012.L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SPXI012.L Payment Methods





















SPXI012.L Shipping Methods













If you have any question about SPXI012.L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com