



### **SPXI012.L Information**

Heisener.com

Part Number SPXI012.L

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 12A 1.5KVDC INLINE

Package Cartridge, Inline, Double Ended

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **SPXI012.L Specifications**

Manufacturer Part NumberSPXI012.LManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Inline, Double EndedSeriesPOWR-GARD? SPXIFuse TypeCartridgeCurrent Rating12AVoltage Rating - AC-Voltage Rating - DC1500V (1.5kV)Response Time-ApplicationsSolar (Photovoltaic)FeaturesIntrinsically SafeClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage15kAMounting TypeIn LinePackage / CaseCartridge, Inline, Double EndedSize / Dimension0.406" Dia x 3.475" L (10.31mm x 88.27mm)Report errors?		
Category  Circuit Protection Electrical, Specialty Fuses  Package Cartridge, Inline, Double Ended Series POWR-GARD? SPXI  Fuse Type Cartridge Current Rating 12A  Voltage Rating - AC Voltage Rating - DC 1500V (1.5kV)  Response Time - Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension  Circuit Protection Electrical, Specialty Fuses Electrical, Specialty Fuses Electrical, Specialty Fuses  Electrical, Specialty Fuses  Electrical, Specialty Fuses  Electrical, Specialty Fuses  POWR-GARD? SPXI  Tartidge Intine, Double Ended Size / Dimension  Circuit Protection Electrical, Specialty Fuses  Electrical, Specialty Fu	Manufacturer Part Number	SPXI012.L
Beckage Cartridge, Inline, Double Ended Series POWR-GARD? SPXI Fuse Type Cartridge Current Rating 12A Voltage Rating - AC - Voltage Rating - DC 1500V (1.5kV) Response Time - Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCartridge, Inline, Double EndedSeriesPOWR-GARD? SPXIFuse TypeCartridgeCurrent Rating12AVoltage Rating - AC-Voltage Rating - DC1500V (1.5kV)Response Time-ApplicationsSolar (Photovoltaic)FeaturesIntrinsically SafeClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage15kAMounting TypeIn LinePackage / CaseCartridge, Inline, Double EndedSize / Dimension0.406" Dia x 3.475" L (10.31mm x 88.27mm)	Category	Circuit Protection
SeriesPOWR-GARD? SPXIFuse TypeCartridgeCurrent Rating12AVoltage Rating - AC-Voltage Rating - DC1500V (1.5kV)Response Time-ApplicationsSolar (Photovoltaic)FeaturesIntrinsically SafeClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage15kAMounting TypeIn LinePackage / CaseCartridge, Inline, Double EndedSize / Dimension0.406" Dia x 3.475" L (10.31mm x 88.27mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 12A Voltage Rating - AC Voltage Rating - DC 1500V (1.5kV) Response Time - Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type In Line Package / Case Size / Dimension  Cartridge Cartridge Cartridge, Inline, Double Ended Size / Dimension  Cartridge Cartridge (Safe) Cartridg	Package	Cartridge, Inline, Double Ended
Current Rating Voltage Rating - AC  Voltage Rating - DC  1500V (1.5kV)  Response Time  - Applications Solar (Photovoltaic)  Features Intrinsically Safe  Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type In Line Package / Case Size / Dimension  12A  - 1500V (1.5kV)	Series	POWR-GARD? SPXI
Voltage Rating - AC  Voltage Rating - DC  1500V (1.5kV)  Response Time  - Applications  Solar (Photovoltaic)  Features  Intrinsically Safe  Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  In Line  Package / Case  Size / Dimension  - Cartridge, Inline, Double Ended  Size / Dimension  - Solar (Photovoltaic)  In Line  - Cartridge, Inline, Double Ended  0.406" Dia x 3.475" L (10.31mm x 88.27mm)	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Applications  Solar (Photovoltaic)  Features  Intrinsically Safe  Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  In Line  Package / Case  Size / Dimension  1500V (1.5kV)  1500V (1.5kV)  1500V (1.5kV)  15kV  1010V (1.5kV)  10	Current Rating	12A
Response Time Applications Solar (Photovoltaic) Features Intrinsically Safe Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension  - Color (Photovoltaic) Intrinsically Safe - Intrinsically Safe - Class - Cartridge, Inline, Double Ended 0.406" Dia x 3.475" L (10.31mm x 88.27mm)	Voltage Rating - AC	-
Applications Solar (Photovoltaic) Features Intrinsically Safe  Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm)	Voltage Rating - DC	1500V (1.5kV)
Features Intrinsically Safe  Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type In Line  Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm)	Response Time	-
Class - Approvals - Coperating Temperature - Streaking Capacity @ Rated Voltage 15kA In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm)	Applications	Solar (Photovoltaic)
Approvals  Operating Temperature  - Breaking Capacity @ Rated Voltage  In Line  Package / Case  Cartridge, Inline, Double Ended  Size / Dimension  O.406" Dia x 3.475" L (10.31mm x 88.27mm)	Features	Intrinsically Safe
Operating Temperature  Breaking Capacity @ Rated Voltage  15kA  Mounting Type  In Line  Package / Case  Cartridge, Inline, Double Ended  Size / Dimension  0.406" Dia x 3.475" L (10.31mm x 88.27mm)	Class	-
Breaking Capacity @ Rated Voltage 15kA  Mounting Type In Line  Package / Case Cartridge, Inline, Double Ended  Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm)	Approvals	-
Mounting Type In Line Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm)	Operating Temperature	-
Package / Case Cartridge, Inline, Double Ended Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm)	Breaking Capacity @ Rated Voltage	15kA
Size / Dimension 0.406" Dia x 3.475" L (10.31mm x 88.27mm)	Mounting Type	In Line
	Package / Case	Cartridge, Inline, Double Ended
Report errors?	Size / Dimension	0.406" Dia x 3.475" L (10.31mm x 88.27mm)
		Report errors?

### **SPXI012.L Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **SPXI012.L Payment Methods**





















## **SPXI012.L Shipping Methods**













If you have any question about SPXI012.L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com