



SPXV025.T Information

Manufa Categor Heisener.com

Part NumberSPXV025.TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE 1500VDC 25 AMP INLINE MIDG

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SPXV025.T Specifications

Manufacturer Part NumberSPXV025.TManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? SPXVFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC1500V (1.5kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage15kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.540" Dia x 3.333" L (13.72mm x 84.65mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? SPXVFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC1500V (1.5kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage15kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Manufacturer Part Number	SPXV025.T
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? SPXVFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC1500V (1.5kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage15kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? SPXVFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC1500V (1.5kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage15kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Category	Circuit Protection
SeriesPOWR-GARD? SPXVFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC1500V (1.5kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage15kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.540" Dia x 3.333" L (13.72mm x 84.65mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC1500V (1.5kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage15kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC Voltage Rating - DC 1500V (1.5kV) Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 25A 25A 26 27 28 29 20 20 21 25A 20 20 20 20 20 20 20 20 20 2	Series	POWR-GARD? SPXV
Voltage Rating - AC Voltage Rating - DC 1500V (1.5kV) Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Holder Package / Case Size / Dimension - Solar (Photovoltaic) - Class - Catrridge, Non-Standard 0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 1500V (1.5kV) 1600V (1.5kV) 16	Current Rating	25A
Response Time - Applications - Solar (Photovoltaic) Features - Class - Approvals - CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension - CE, UR -	Voltage Rating - AC	-
Applications Solar (Photovoltaic) Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Voltage Rating - DC	1500V (1.5kV)
Features - Class - CE, UR Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Response Time	-
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Applications	Solar (Photovoltaic)
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 15kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 15kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Class	-
Breaking Capacity @ Rated Voltage 15kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Approvals	CE, UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Breaking Capacity @ Rated Voltage	15kA
Size / Dimension 0.540" Dia x 3.333" L (13.72mm x 84.65mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.540" Dia x 3.333" L (13.72mm x 84.65mm)
		Report errors?

SPXV025.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SPXV025.T Payment Methods





















SPXV025.T Shipping Methods













If you have any question about SPXV025.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com