

Heisener.com

SQBW3010RJFASTON

SQBW3010RJFASTON Information

Part Number SQBW3010RJFASTON

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 10 OHM 5% 30W

Package Radial, Rectangular Case

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SQBW3010RJFASTON Specifications

Manufacturer Part NumberSQBW3010RJFASTONManufacturerTE Connectivity Passive ProductCategoryResistorsPackageRadial, Rectangular CaseSeriesSQ, CGSResistance10 OhmsTolerance±5%Power (Watts)30WCompositionWirewoundTemperature Coefficient±300ppm/°COperating Temperature-55°C ~ 250°CFeaturesFlame Proof, Moisture Resistant, SafetyCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension2.953" L x 0.748" W (75.00mm x 19.00mm)Height - Seated (Max)-Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseRadial, Rectangular CaseFailure Rate-		
CategoryResistorsPackageRadial, Rectangular CaseSeriesSQ, CGSResistance10 OhmsTolerance±5%Power (Watts)30WCompositionWirewoundTemperature Coefficient±300ppm/°COperating Temperature-55°C ~ 250°CFeaturesFlame Proof, Moisture Resistant, SafetyCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension2.953" L x 0.748" W (75.00mm x 19.00mm)Height - Seated (Max)-Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseRadial, Rectangular CaseFailure Rate-	Manufacturer Part Number	SQBW3010RJFASTON
Chassis Mount Resistors Package Radial, Rectangular Case Series SQ, CGS Resistance 10 Ohms Tolerance ±5% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±300ppm/°C Operating Temperature -55°C ~ 250°C Features Flame Proof, Moisture Resistant, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 2.953" L x 0.748" W (75.00mm x 19.00mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate	Manufacturer	TE Connectivity Passive Product
PackageRadial, Rectangular CaseSeriesSQ, CGSResistance10 OhmsTolerance±5%Power (Watts)30WCompositionWirewoundTemperature Coefficient±300ppm/°COperating Temperature-55°C ~ 250°CFeaturesFlame Proof, Moisture Resistant, SafetyCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension2.953" L x 0.748" W (75.00mm x 19.00mm)Height - Seated (Max)-Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseRadial, Rectangular CaseFailure Rate-	Category	Resistors
SeriesSQ, CGSResistance10 OhmsTolerance±5%Power (Watts)30WCompositionWirewoundTemperature Coefficient±300ppm/°COperating Temperature-55°C ~ 250°CFeaturesFlame Proof, Moisture Resistant, SafetyCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension2.953" L x 0.748" W (75.00mm x 19.00mm)Height - Seated (Max)-Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseRadial, Rectangular CaseFailure Rate-		Chassis Mount Resistors
Resistance10 OhmsTolerance±5%Power (Watts)30WCompositionWirewoundTemperature Coefficient±300ppm/°COperating Temperature-55°C ~ 250°CFeaturesFlame Proof, Moisture Resistant, SafetyCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension2.953" L x 0.748" W (75.00mm x 19.00mm)Height - Seated (Max)-Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseRadial, Rectangular CaseFailure Rate-	Package	Radial, Rectangular Case
Tolerance ±5% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±300ppm/°C Operating Temperature -55°C ~ 250°C Features Flame Proof, Moisture Resistant, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 2.953" L x 0.748" W (75.00mm x 19.00mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Series	SQ, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±300ppm/°C Operating Temperature -55°C ~ 250°C Features Flame Proof, Moisture Resistant, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 2.953" L x 0.748" W (75.00mm x 19.00mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Failure Rate -	Resistance	10 Ohms
Composition Wirewound Temperature Coefficient ±300ppm/°C Operating Temperature -55°C ~ 250°C Features Flame Proof, Moisture Resistant, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 2.953" L x 0.748" W (75.00mm x 19.00mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Tolerance	±5%
Temperature Coefficient ±300ppm/°C Operating Temperature -55°C ~ 250°C Features Flame Proof, Moisture Resistant, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 2.953" L x 0.748" W (75.00mm x 19.00mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Power (Watts)	30W
Operating Temperature -55°C ~ 250°C Features Flame Proof, Moisture Resistant, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 2.953" L x 0.748" W (75.00mm x 19.00mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Composition	Wirewound
Features Flame Proof, Moisture Resistant, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 2.953" L x 0.748" W (75.00mm x 19.00mm) Height - Seated (Max) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Temperature Coefficient	±300ppm/°C
Coating, Housing Type Mounting Feature Brackets Size / Dimension 2.953" L x 0.748" W (75.00mm x 19.00mm) Height - Seated (Max) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Operating Temperature	-55°C ~ 250°C
Mounting Feature Brackets Size / Dimension 2.953" L x 0.748" W (75.00mm x 19.00mm) Height - Seated (Max) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Features	Flame Proof, Moisture Resistant, Safety
Size / Dimension 2.953" L x 0.748" W (75.00mm x 19.00mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Coating, Housing Type	Ceramic
Height - Seated (Max) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Mounting Feature	Brackets
Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Size / Dimension	2.953" L x 0.748" W (75.00mm x 19.00mm)
Package / Case Radial, Rectangular Case Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Quick Connects, 0.250" (6.35mm)
	Package / Case	Radial, Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

SQBW3010RJFASTON Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SQBW3010RJFASTON Payment Methods



















SQBW3010RJFASTON Shipping Methods













If you have any question about SQBW3010RJFASTON, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com