

SR-7601 Information

Heisener.com

Part Number SR-7601

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category

Signal Relays, Up to 2 Amps

RELAY GEN PURPOSE 4PDT 2A 26.5V **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SR-7601 Specifications

Manufacturer Part NumberSR-7601ManufacturerTE Connectivity Aerospace, Defense and MarineCategoryRelaysPackage-SeriesMilitary, MIL-R-39016/40, SR, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current68mACoil Voltage26.5VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)1.4 VDCOperate Time7msRelease Time7msFeatures-Mounting TypeChassis MountTermination StyleSolder Hook		
CategoryRelaysPackage-SeriesMilitary, MIL-R-39016/40, SR, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current68mACoil Voltage26.5 VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage28 VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)1.4 VDCOperate Time7msRelease Time7msFeatures-Mounting TypeChassis MountTermination StyleSolder Hook	Manufacturer Part Number	SR-7601
Package-SeriesMilitary, MIL-R-39016/40, SR, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current68mACoil Voltage26.5VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)1.4 VDCOperate Time7msRelease Time7msFeatures-Mounting TypeChassis MountTermination StyleSolder Hook	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Series Military, MIL-R-39016/40, SR, CII Relay Type General Purpose Coil Type Non Latching Coil Current 68mA Coil Voltage 26.5VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 1.4 VDC Operate Time 7ms Release Time 7ms Features - Mounting Type Chassis Mount Termination Style Solder Hook	Category	Relays
SeriesMilitary, MIL-R-39016/40, SR, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current68mACoil Voltage26.5VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)1.4 VDCOperate Time7msRelease Time7msFeatures-Mounting TypeChassis MountTermination StyleSolder Hook		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current68mACoil Voltage26.5VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)1.4 VDCOperate Time7msRelease Time7msFeatures-Mounting TypeChassis MountTermination StyleSolder Hook	Package	-
Coil Type Non Latching Coil Current 68mA Coil Voltage 26.5 VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 1.4 VDC Operate Time 7ms Release Time 7ms Features - Mounting Type Chassis Mount Termination Style Solder Hook	Series	Military, MIL-R-39016/40, SR, CII
Coil Current68mACoil Voltage26.5VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)1.4 VDCOperate Time7msRelease Time7msFeatures-Mounting TypeChassis MountTermination StyleSolder Hook	Relay Type	General Purpose
Coil Voltage 26.5VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 1.4 VDC Operate Time 7ms Release Time 7ms Features - Mounting Type Chassis Mount Termination Style Solder Hook	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 1.4 VDC Operate Time 7ms Release Time 7ms Release Time 7ms Features - Mounting Type Chassis Mount Termination Style Solder Hook	Coil Current	68mA
Contact Rating (Current) Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 1.4 VDC Operate Time 7ms Release Time 7ms Features - Mounting Type Chassis Mount Termination Style	Coil Voltage	26.5VDC
Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 1.4 VDC Operate Time 7ms Release Time 7ms Features - Mounting Type Chassis Mount Termination Style Solder Hook	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 1.4 VDC Operate Time 7ms Release Time 7ms Features - Mounting Type Chassis Mount Termination Style Solder Hook	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 7ms Release Time 7ms Features - Mounting Type Chassis Mount Termination Style 1.4 VDC 7ms Chassis Mount Solder Hook	Switching Voltage	28VDC - Nom
Operate Time 7ms Release Time 7ms Features - Mounting Type Chassis Mount Termination Style Solder Hook	Turn On Voltage (Max)	14 VDC
Release Time 7ms Features - Mounting Type Chassis Mount Termination Style Solder Hook	Turn Off Voltage (Min)	1.4 VDC
Features - Mounting Type Chassis Mount Termination Style Solder Hook	Operate Time	7ms
Mounting Type Chassis Mount Termination Style Solder Hook	Release Time	7ms
Termination Style Solder Hook	Features	-
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Solder Hook
		Report errors?

SR-7601 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SR-7601 Payment Methods



















SR-7601 Shipping Methods













If you have any question about SR-7601, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com